

## IP BULLET CAMERA

### 4 MP IR Outdoor Bullet Camera



The 0E-40BF36WDR is a 4 MP (2592x1520) bullet camera constructed with a 3.6mm lens. This 4 MP Camera is IP67 rated and provides HD Image quality and is ideal for numerous indoor/outdoor applications such as commercial applications, home or office use as well as monitoring hallways, unattended storage areas and various other installation applications.

- 3.6 mm lens · 24 IR LEDs
- IR Distance: 30 m/100 ft
- 3-axis Gimbal · 3D Digital Noise Reduction
- True Wide Dynamic Range
- Onvif Profile S Supported
- IP 67 Rated
- PoE/12 VDC
- 5 Year Warranty

PART #: 0E-40BF36WDR

UPC: 811914027997

LENGTH: 8.9"

HEIGHT: 2.7"

WEIGHT: 18.34 ounces

FOR MORE INFORMATION,  
CONTACT YOUR ADI SALES PERSON.

FOR TECHNICAL SUPPORT: 1-888-888-8997

ONVIF



# Specifications

<b>Model</b>	0E-40BF36WDR
<b>Image Sensor</b>	1/3" Progressive Scan CMOS
<b>Min. illumination</b>	Color :0.05Lux@(F1.2,AGC ON);B/W: 0 Lux@(IR LED ON)
<b>Day &amp; Night</b>	ICR
<b>Shutter Speed</b>	1/5-1/20000
<b>Auto Iris</b>	Fixed
<b>Wide Dynamic Range</b>	WDR >120dB
<b>Digital Noise Reduction</b>	2D/3D
<b>Lens</b>	3.6mm
<b>FOV</b>	85°
<b>IR LED</b>	24pcs
<b>IR Range</b>	30m
<b>IMAGE</b>	
<b>Video Compression</b>	H.265/H.264/ MJPEG
<b>Bit Rate (CBR/VBR)</b>	Main stream: 1080P: 500Kbps~12Mbps , 720P: 200Kbps~8Mbps ; Sub stream 100Kbps~6Mbps
<b>Audio Compression</b>	G.711 ,RAW_PCM
<b>Max. Resolution</b>	2592x1520/20fps
<b>Stream</b>	Stream 1 2592x1520/2560x1440/2304x1296/1920x1080/1280x720 Stream 2 D1 to QVGA Stream 3 2592x1520/2560x1440/2304x1296/1920x1080/1280x720/D1/VGA/ 640 x 360/CIF/QVGA
<b>Image Setting</b>	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
<b>HLC</b>	Yes
<b>9:16 Corridor mode</b>	Yes
<b>ROI</b>	Yes
<b>Defog</b>	N/A
<b>NETWORK</b>	
<b>Network Protocols:</b>	IPv4,802.1x,HTTP,HTTPS,TCP/IP,UDP/IP,RTSP,DHCP,NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ICMP ,IGMP, Unicast and Multicast
<b>Alarm Trigger</b>	Motion Detection, Network Disconnect, Disk Alarm
<b>RTSP Video</b>	Standard RFC2326, Support QuickTime / VLC Player.
<b>Security</b>	User security authentication, Reset, Hardware Watch Dog
<b>Web Language</b>	English, Chinese, Polish, Italian, Portuguese, Spanish. Russian, French, Czech, Hungarian
<b>System Compatibility</b>	Onvif Profile S Supported
<b>Interface</b>	
<b>Ethernet</b>	1 Ethernet (10/100 Base-T) RJ-45 Connector
<b>GENERAL</b>	
<b>Power Supply</b>	DC12V/POE
<b>Power Consumption</b>	2.5W(IR LED OFF); 5W (IR LED ON)
<b>Operating Temperature</b>	Starting Temperature: -10°C ~ 50°C (14°F ~ 122°F) Working Temperature: -20°C ~ 50°C (-4°F ~ 122°F)
<b>Operating Humidity</b>	0% - 90% RH
<b>Ingress Protection</b>	IP67
<b>Product Dimensions</b>	Φ228*69mm
<b>Product Weight</b>	520g