P3POE9-30G



Power Over Ethernet (PoE) Switch, Unmanaged, Full Gigabit - 250W Max



DESCRIPTION

The P3POE9-30G is an unmanaged Power over Ethernet (PoE) switch designed for wiring LAN (WAN) access points, IP security cameras, VoIP telephone and other low port density installations. The P3POE9-30 provides 30W POE power, full load on all ports. The P3POE9-30 is a case-shaped device with a chassis of 1U high. It provides (8) 10/100/1000 Base-TX ports and (1) 10/100/1000 uplink port.

FEATURES

- Conforms to IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3af, IEEE802.3at
- Provides (8) 10/100/1000Base-TX ports and (1) 10/100/1000 Uplink port
- IEEE802.3x Flow control
- High back-plane bandwidth 18Gbps
- Plug and play operation
- Surge protection for power port and data ports
- EMI standards complies with FCC, CE class B

SPECIFICATIONS

Item Summary	Description
Fixed Port	(8) 10/100/1000 Base-TX ports – (1) 10/100/1000 Uplink port
LED Indicators	PWR, PoE, Link/Act VLAN LED.
Input Voltage	100V∼240V AC, 50/60Hz
Power Consumption	250W
Operating Temperature	0°C∼40°C - 32°F ∼113°F
Storage Temperature	-10°C∼70°C
Operating Humidity	10%~90% (non-condensing).
Thermal Methods	Built-in Noiseless Fan.
Switching Capacity	18G
MAC Address Table	4K
Traffic Control	IEEE 802.3x full-duplex flow control.
PoE	
PoE Port	(8) 10/100/1000 Base-TX ports.
PoE Standard	IEE802.af, per port 30W.
Pin Assignment	V- (RJ45 Pin 1, 2), V+ (RJ45 Pin 3, 6).