



VOSKER V200

LTE Wireless Solar Powered Security Camera



No Wi-Fi? No problem.

Ideal for a construction site, farm, country house, vacation home, rental property, parking lot or marina. Monitor anything, anywhere! No need for Wi-Fi thanks to LTE based mobile connectivity to transmit photos to your phone and get mobile alerts.



Works without Wi-Fi thanks to LTE connectivity



Built-in solar panel for extended battery life



Monitor job site, farm, cabin or any other remote locations



Day and night photos with custom alerts on the mobile app



Preactivated SIM card, SD card and mount included



Weather-Resistant and rugged design



Night vision and automatic motion detection



Rechargeable battery pack, 8 AA batteries or 12V



FREE mobile security plan offered



VOSKER two (2) year limited warranty.



For more information or to buy an international model, contact support@vosker.com



GENERAL SPECIFICATIONS - V200

PHOTO

Photo Resolution	Full HD 1920×1080 on SD card and 600×338 on mobile app
File Format	JPG
Time Lapse Mode	Customizable preset intervals
Multi Photo Mode	Up to 3 photos per detection
Information Stamped on Photos	Date, time and temperature (°C/°F)
Operation Mode	Photo, video, time lapse or photo + time lapse
Capture Mode	Colored photos by day and black and white by night (with IR) – White IR LED with smoke glass window (super low glow)
Night Vision (IR Setting)	Blur reduction, boost, and optimal
Optical Field of View	43.6°

VIDEO

Video Access	SD card only
Video Resolution	1080p, 10 fps
Video File Format	AVI
Video Length	10 s, 30 s, 60 s, and 90 s
Photo First	Takes a picture before recording. Make sure to enable PHOTO FIRST option in the mobile app to allow the camera to send a photo to your phone for every video recorded.
Capture Mode	Colored photos by day and black and white by night (with IR)
Audio Recording	Yes



GENERAL SPECIFICATIONS - V200

MEMORY

Capacity	External memory: SD/SDHC card up to 32 GB (8 GB card included)
-----------------	--

VIEWING

Built-in Screen	2.16" TFT-ACL (configuration or viewing screen)
------------------------	---

Zoom and Pan Functions	Available
-------------------------------	-----------

Viewing Functions	9 photos as tiles or cycle through pictures
--------------------------	---

Viewing Options	View/zoom, date and time, lock/unlock, delete, delete all, and format SD card
------------------------	---

BATTERY/POWER SOURCE

Lithium or Standard Batteries	8 × AA (not included) or lithium battery pack V-LIT-B (not included) required to operate the camera
--------------------------------------	---

12 V Power Jack	12 V battery (V-CASE-12V) or 12 V adaptor (V-AT12V)
------------------------	---

SOLAR SYSTEM

Solar Panel	Built-in solar panel
--------------------	----------------------

Internal Battery (Solar Tech)	4000 mAh lithium internal battery
--------------------------------------	-----------------------------------

Maximum Voltage Accepted	12 V
---------------------------------	------

Charging Time for Internal Battery	Charge for 24 to 48 hrs before first use
---	--



GENERAL SPECIFICATIONS - V200

DETECTION SYSTEM

Detection System	PIR
Detection Angle	50°
Motion Sensor	1 sensor for a total of 5 detection zones
Detection Range	100 ft
Optional Delay Between Detections	Preset delays of 10 s, 1 min, 3 min, 5 min, 10 min, 15 min and 30 min
Trigger Time	0.07 s

NIGHT VISION/FLASH

LED	42 LED(45°)
Type	White LED super low glow
Flash Range	100 ft
Exposition	Automatic adjustment of infrared light strength

DIMENSIONS

Camera Body	4.4" W × 3.3" D × 7.5" H
--------------------	--------------------------



GENERAL SPECIFICATIONS - V200

CELLULAR

SIM Card	Included
Mobile Connectivity	LTE
Reception	Mobile app or web app
Required Carrier	No specific carrier
Synchronisation Frequency	1/day, 2/day, 6/day, 12/day, or each detection
GPS Localisation System	Yes, when enabled
Camera Configuration	Unit screen, web app or mobile app
Trial Period	30 days of unlimited photos to test all features.

GENERAL CONFIGURATION

Language	English, French, Spanish, and German
Sensitivity Settings	Low, normal and high
Date Format	mm/dd/yyyy or dd/mm/yyyy
Photo Stamp Information	Yes, when enabled
Temperate Units	°C or °F
Information in "About" Menu	S/W, H/W, model, device name, IMEI, SIM, region, and modem version
Schedule Set-Up	Complete control over schedule
Time Format	12H or 24H



GENERAL SPECIFICATIONS - V200

OTHER

External Antenna	Included
External Extra Long Antenna	Sold separately
Mounting Bracket	Adjustable mounting arm and strap included
Operating Temperature Range	40°C to -40°C
Certifications	FCC, CE, IP65 weather-resistant
Warranty	www.vosker.com/warranty-and-repair/