



PRODUCT DESCRIPTION

- Horizontal 10" Wall Panel for Mounting in 89D Bracket
- This patch panel is designed for 22-26 AWG solid conductors
- Horizontal termination

CONSTRUCTION CHARACTERISTICS

- Color marking of conductors according to T568B and T568A
- Numeral marking of ports on the front side of the panel
- Space for additional marking
- Color and numeral marking of IDC modules on the rear side of the panel
- Hyperline patch cord usage provides the best connection
- 110 type punch down tool is used for cable termination

MATERIALS

- Front Plate : Fireproof ABS UL-94V0
- IDC: Phosphor Bronze and Fireproof UL-94V0 PCT(PC+PBT)
- PCB: FR-4 / UL-94V0 / 1.6mm
- Contacts: Phosphor Bronze 8P8C & 50 micro inches gold plated
- 89D Bracket : ABS

ELECTRICAL CHARACTERISTICS

- Insulation Resistance : 500M ohms (min.)
- Contact Resistance : 20m ohms
- Current Rating : 1.5 Amps
- DC Resistance : 0.1 ohms (max.)
- Dielectric withstand voltage: 1000 V AC RMS, 60Hz/1min

ORDERING

Part Number	Description
PPWI-12-8P8C-C6	Patch Panel 10", 1U, 12-port RJ-45, category 6, 110 IDC

