



Hi-Speed USB Desktop Hub

10 USB 2.0 Type-A Ports, Bus or AC Power

Part No.: [161572](#)

EAN-13: 0766623161572 | UPC: 766623161572

Powerful USB performance in a multi-port hub

The Manhattan Hi-Speed USB Desktop Hub easily expands USB access for a desktop or notebook computer to connect more peripherals and mobile devices. With 10 extra high-speed, backward-compatible ports, the Manhattan Hi-Speed USB Desktop Hub can manage almost any digital enthusiast's growing collection of USB-enabled devices. It's ideal for recharging MP3 players, cell phones, digital cameras and other mobile accessories and connecting keyboards, mice, Web cameras, flash drives, card readers and more. The compact and durable plastic case features the power and hub-to-PC ports on the side panel to help better organize connections and minimize cable clutter. Plug and Play with hot-swap capabilities, Windows 7/8.1/10 and Mac compatibility, and data transfer speeds up to 480 Mbps help the Manhattan Hi-Speed USB Desktop Hub consolidate numerous, less-capable hubs into a single USB solution.

Features:

- Provides 10 Hi-Speed USB ports for additional peripherals
- Replaces less-capable hubs with compact, multiport design
- Multiple Transaction Translator supports low-speed and high-bandwidth USB devices for optimum performance
- Conveniently recharges mobile devices and connects flash drives, receivers, card readers and more
- Overcurrent protection; hot-swappable

- Compatible with all USB-equipped computers
- Plug and play; Windows 7/8.1/10 and Mac compatible
- Three-year warranty

Specifications:

Standards and Certifications

- USB 2.0, USB 1.1, USB 1.0
- FCC
- CE

Ports

- Transfer speeds: 1.5 / 12 / 480 Mbps
- One type-B upstream port
- 10 type-A downstream ports
- 5 VDC port
- Up to 500 mA power, all ports*
- *hub must be plugged into a PC or Mac to charge phones

Physical

- Dimensions: 190 (H) x 37 (W) x 21 (D) mm (7.5 x 1.5 x 0.8 in.)
- Weight: 140 g (4.94 oz.)
- USB type-A to type-B cable: 150 cm (59 in.)
- Housing: plastic
- LED power indicator

Power Adapter

- cUL, FCC
- Input: 100 – 240 V, 50/60 Hz; 0.4 A, maximum
- Output: 5 V / 2 A
- Cable: 1.8 m (6 ft.)

System Requirements

- USB-enabled PC or Mac system
- Windows 2000/XP/Vista/7/8.1/10 or Mac OS 9 or above
- Available USB port

Operating Environment

- Operation temperature: 0 - 40°C (32 - 104°F)
- Storage temperature: -10 - 65°C (14 - 149°F)

Package Contents

- Hi-Speed USB Desktop Hub
- USB cable
- Power adapter
- Instructions

