



# Gigabit Fiber SFP Optical Transceiver Module

1000Base-SX (LC) Multi-Mode Port, 550 m

Part No.: **545006**

EAN-13: 0766623545006 | UPC: 766623545006

---

## Gigabit Fiber SFP Optical Transceiver Module

The line of Intellinet Network Solutions Small Form Factor Pluggable (SFP) Transceivers provides customers with a combination of performance and affordability. These mini-GBIC (Gigabit Interface Converter) modules come in a metal housing that reduces electromagnetic interference and increases their durability.

### Small Size for High-Density Fiber Connections

The transceiver comes in a mini-GBIC form factor, making it ideal for environments that require many fiber connections by taking up less space in your cabinet and/or computer room.

### Multi-Vendor Compatible

Compatibility in your network is everything, and the Intellinet SFP Transceiver Module (model 545006) delivers. Use it with any Intellinet SFP equipped network switch or any other MSA (multi source agreement) compliant SFP enabled switch. And since the Intellinet SFP transceiver module is set to broadcast the vendor pn GLC-SX-MM, compatibility to your Cisco gear is provided.

### Hot-Pluggable

No need to power down your LAN switch in order to install or remove the transceiver. This makes it very convenient and easy for you to make adjustments to your network that allow your business to keep pace with the changing demands of the market.

## Features:

- Data transfer rate: 1000 Mbps
- One 1000Base-SX multi-mode fiber LC duplex port
- Distance support: up to 550 m (50/125  $\mu\text{m}$  cable) or 220 m (62.5/125  $\mu\text{m}$  cable)
- Wavelength: 850 nm
- SFP standard form factor
- Compliant with SFP Transceiver MSA specifications
- Equivalent to the Cisco GLC-SX-MM transceiver
- Supports hot-plugging
- Three-Year Warranty

## Specifications:

### Standards

- IEEE 802.3z (Fiber Optic Gigabit Ethernet)

### General

- Media support:
  - 1000Base-SX multi-mode 50/125  $\mu\text{m}$  fiber
  - 1000Base-SX multi-mode 62.5/125  $\mu\text{m}$  fiber
- Connector: fiber LC duplex port, 1000Base-SX
- Distances:
  - 550 m (50/125  $\mu\text{m}$  fiber cable)
  - 220 m (62.5/125  $\mu\text{m}$  fiber cable)
- Wavelength: 850 nm
- Fiber power budget
  - Maximum TX power: -3 dBm
  - Minimum TX power: -8 dBm
  - Sensitivity: -20 dB
  - Power budget: 8 dB
- Design: SFP (small form factor pluggable)
- Certifications: FCC Class B, CE, RoHS, IEC-60825

### Power

- Power requirement: 3.3 V
- Power consumption: 1.0 watt (maximum)

### Environmental

- Dimensions: 55 (L) x 13 (W) x 12 (H) mm (2.2 x 0.5 x 0.5 in.)
- Weight: 15 g (0.5 oz.)
- Operating temperature: 0 - 70°C (32 - 158°F)
- Typical operating temperature: 34.8°C (94.64°F)
- Operating humidity: 5 - 95% RH, non-condensing
- Storage temperature: -40 - 85°C (-40 - 185°F)

#### Package Contents

- Gigabit Fiber SFP Optical Transceiver Module

