



5822T

Wireless Tilt Sensor Transmitter

The Honeywell Home 5822T Wireless Tilt Sensor Transmitter is designed to mount vertically on surfaces that tilt horizontally when opened – providing an easy way to secure garage doors or basement tilt windows. Any time the sensor detects tilt movement, a notification is transmitted to the control panel. The sensor can be programmed as a monitored or notification only zone. Includes cover tamper and battery supervision.



FEATURES AND BENEFITS

- Easy to install – use double sided tape or screws (included). Screws must be used in installations where temperatures can drop to 32°F (0°C) or below.
- Internal LED for easy programming
- Reliable 5800 Series Wireless
- Case tamper and battery supervision

SPECIFICATIONS

Battery (included)*: 1 x 3 V, Lithium
*Panasonic CR123A, Duracell DL123, Duracell DL123A or Honeywell Home 466

Operating Temperature:
0°F to +131°F (-17°C to +55°C)

Relative Humidity:
95% max. (non-condensing)

Dimensions: 1-9/16" W x 3-1/16" H x 1-3/16" D (40 mm x 78 mm x 30 mm)

Compatibility:

- Honeywell Home 5800 Series Wireless
 - Loop 1 terminals
 - Loop 3 tilt sensor
- FCC part 15, Class B verified
IC, ICES-003, Class B verified

ORDERING

5822T	Wireless Tilt Sensor Transmitter
-------	----------------------------------

For more information

security.honeywellhome.com/hsc



Resideo Technologies, Inc.

2 Corporate Center Drive, Suite 100
P.O. Box 9040
Melville, NY 11747
1-800-645-7492
resideo.com

L/5822TD/D | 06/19
© 2019 Resideo Technologies, Inc.
This product is manufactured by Resideo and its affiliates. The Honeywell Home trademark is used under license from Honeywell International Inc. All rights reserved.