

Overview:

The HDMI over IP Extender Kit with PoE allows HDMI equipment to be connected up to 330ft (100m) @ 1080p via one (1) Cat5e/6 unshielded twisted pair cable in a point-to-point configuration. Point-to-multipoint and multipoint-to-multipoint is possible by connecting several Transmitters and Receivers to the same Ethernet network.

The MuxLab Pro Digital Network Controller (500811) is available to simplify configuration and control and allows for third party smartphone and tablet management.


The Transmitter (500752-TX) and Receiver (500752-RX) also support PoE (PD) if used with a PoE (PSE) Ethernet Switch. The kit comes with one (1) Transmitter and one (1) Receiver. The IR Emitter and IR Sensor, if required, may be purchased separately for IR based remote control applications.

For the point-to-multipoint and multipoint-to-multipoint configuration the Ethernet switch must have Gigabit ports, DHCP Server capability and IGMP communications protocol. We recommend using the Cisco SG300 Series Managed Switches.



Features:

- HDMI 1.3
- Supports up to 1080p resolutions
- Motion JPEG compression with Very low latency
- Supports 100's of Transmitters and Receivers, depending on network bandwidth
- Supports point-to-point, point-to-multipoint and multipoint-to-multipoint applications
- Transmission up to 330ft (100m) over Cat5e/6
- Up to 390ft (120m) between the TX and RX when no LAN switch is used
- Supports IR transmission for remote control
- PoE powered
- Control via any web device (mobile, tablet) with use of model 500811 (Pro Digital Network Controller)

Environment	HDMI 1.3a
Devices	DVD, plasma, projectors, monitors, TV, PC, laptops, servers supporting HDMI.
Video Transmission	Transparent to the user
Video Bandwidth	225MHz
Signals	HDMI 1.3a protocol
Connectors	One (1) HDMI receptacle. One (1) RJ45S for Cat 5e/6 unshielded or shielded twisted pair. One (1) 3.5mm jacks for IR emitter/sensor. Four (4) DIP Switches for device ID addressing. <i>Note: Cables not included.</i>
Maximum Distance <i>Based on a maximum length of 6.6ft (2m) of HDMI cable per end.</i>	Cat5e/6: 330ft (100m) up to 1080P Cat5e/6: 400ft (120m) when used point to point without hub. <i>Note: When installed in an electrically noisy environment, an STP cable must be used. Also, cross-connection reduces the effective distance depending on the grade of twisted cable used.</i>
Latency	One (1) Frame
Compression	Motion JPEG
Network Bandwidth	60Mbps
Network Requirement	100BaseT for Point to Point; 1000BaseT for other configuration
IR Frequency	38 to 56KHz
RJ45 Pin Configuration <i>Reverse Polarity Sensitive. Use EIA/TIA 568A or 568B straight-through wiring.</i>	RJ45 Link Pin 1 (R) Pin 2 (T) Pin 3 (R) Pin 6 (T) Pin 4 (R) Pin 5 (T) Pin 7 (R) Pin 8 (T) 

Cable	One (1) Cat 5e/6 or better twisted pair cables required
Power Supply	This device supports PoE (PD), an external power supply is not included. It is intended to be powered via a PoE (PSE) Ethernet Switch. If required, an optional power supply (500992) may be purchased separately.
PoE	IEEE 802.3af
Power Consumption	Transmitter: 2.9Watt Receiver: 1.8Watt
Temperature	Operating: 0° to 40°C Storage: -20° to 85°C Humidity: Up to 95% non-condensing
Enclosure	Metal black
Dimensions	3.70" x 3.68" x 0.97" (94 x 93.5 x 24.6mm)
Weight	1.1lbs (0.5kg)
Compliance	Regulatory: FCC, CE, RoHS Flammability: 94V0
Warranty	2 years
Order Information	500752 HDMI over IP Extender Kit with PoE (UPC: 627699007525) 500752-TX HDMI over IP Extender TX with PoE (UPC: 627699907528) 500752-RX HDMI over IP Extender RX with PoE (UPC: 627699807521)
Accessories <i>(These items are sold separately)</i>	500990 IR Emitter, and 500991 IR Sensor 500992 Univ. Power Supply 5VDC/1.2A US/UK/EU Blade

HDMI over IP Extender Kit with PoE 500752

Typical Application:

