



ECM-44 series

Lavalier Microphones

- Omni-directional, electret condenser microphone
- Superior sound quality
- Frequency response: 40 Hz to 15 kHz
- Sensitivity: -40 dB SPL (10 mV) (0 dB = 1V/Pa, at 1 kHz)
- Microphone head: 8.5 mm (11/32 inch) dia. X 14.5 mm (19/32 inches), approx. 2 g (0.07 oz)
- Cable length: 1.2 m (3.9 feet)
- Supplied accessories: holder clip (1, single/horizontal type), Urethane wind screen (1), microphone case (1)
- Two types of connections available;
 - ECM-44BC;** Supplied with SMC9-4S connector for use with WRT-822A/822B/860A
 - ECM-44BMP;** Supplied with 3-pole Mini Jack with a stable lock mechanism for use with WRT-805A/805B



ECM-55 Series

Lavalier Microphones

- Uni-directional electret condenser microphone
- Frequency response tailored for enhanced presence and improved voice quality in lavalier applications
- Frequency response: 30 Hz to 18 kHz
- Sensitivity: -38.5 dB (11.9 mV) (0 dB = 1V/Pa, at 1 kHz)
- Microphone head: 10.6 dia. x 21 mm (7/16 dia. x 27/32 inch) approx. 6.5 g (0.2 oz)
- Supplied accessories: Holder clip (1), Metal-mesh wind screen (1)
- Two types of connections are available:
 - ECM-55BPT;** 3.0 m (9.8 feet) cable without battery or connector (pig tail connection)
 - ECM-55BC;** 1.2 m (3.9 feet) cable terminating in SMC9-4P type connector for use with WRT-822B/860A



ECM-66 Series

Lavalier Microphones

- Uni-directional electret condenser microphone
- Designed for instrumental applications
- Frequency response: 70 Hz to 14 kHz
- Sensitivity: -36.5 dB (15 mV) (0 dB = 1V/Pa, at 1 kHz)
- Microphone head: 10.6 dia. x 24.2 mm (7/16 dia. x 31/32 inch) approx. 7.0 g (0.3 oz)
- Supplied accessories: Holder clip (1), Urethane wind screen (1)
- Two types of connections are available:
 - ECM-66BPT;** 3.0 m (9.8 feet) cable without battery or connector (pig tail connection)
 - ECM-66BC;** 1.2 m (3.9 feet) cable terminating in SMC9-4P type connector for use with WRT-822B/860A



ECM-77 series

Lavalier Microphones

- High performance, ultra miniature, microphone
- Omni-directional, electret condenser microphone
- Frequency response: 40 Hz to 20 kHz
- Sensitivity: -39.0 dB (11.2 mV) (0 dB = 1V/Pa, at 1 kHz)
- Microphone head: 5.6 mm (1/4 inch) dia. x 12.5 mm (1/2 inches), approx. 1.5g (0.05 oz)
- Cable length: 1.2 m (3.9 feet)
- Supplied accessories: holder clips (2, single/horizontal type and single/vertical type), Metal-mesh wind screen (1), microphone case (1)
- Two types of connections available:
 - ECM-77BC/FC;** Supplied with SMC9-4S connector for use with WRT-822A/822B/860A
 - ECM-77BMP;** Supplied with 3-pole Mini Jack with a stable lock mechanism for use with WRT-805A/805B

EC-0.4CM

SMC9-4P

- XLR male adapter cable

A-8278-057-A

Bracket (available only through Sony Service Parts)

- For mounting any Sony portable tuner (with tuner supplied hardware) to most Sony professional camcorders which work with Sony Lithium-Ion batteries

EC-1.5CF

Microphone Cable

- Fitted with an XLR female connector and SMC9-4P connector
- Allows a microphone with a 3-pin male XLR output connector to be connected to WRT-822A/822B/860A transmitter
- Cable length: 1.5 m (4.9 feet)

GC-0.7MP/1 Guitar Cable

- Used with WRT-805A/805B Body Pack Transmitter
- Special active guitar cable for high quality re-production of guitar sound
- 3-pole mini plug with a lock mechanism for secure cable clamping
- 5.5 mm (7/32 inch) dia. x 0.7 m (2.3 feet)