




- 4MP Resolution
- All-in-one cameras
- No Server Required
- 256GB 128GB 64GB Storage
- 30x Up to 30 Cameras
- 2.8-12mm Auto Focus Lens
- 5 YEAR Warranty

Dimensions

unit: inch (mm)



Specifications



Designed and engineered in U.S.A and Korea

IMAGE	
Image sensor	4MP 1/3" CMOS
Total pixels	2688 (H) x 1520 (V)
Minimum scene illumination	0.2 lux (color) 0.0 lux (B/W)
Video output	Local video output CVBS 1.0V p-p (75Ω) 4:3 aspect ratio
Resolution	4MP (2560 x 1440)
LENS	
Focal length	2.8-12mm, F1.4
Lens type	Motorized zoom auto-focus p-iris lens
Field of view (FoV)	87° - 32°
IR distance	100ft range IR
Optical zoom	x4.2 optical zoom
OPERATIONAL	
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/30-1/32000
Slow shutter	1-1/5, 1/7.5, 1/10
Auto gain control	Auto
Day and night	Auto, day (Color), night (B/W)
Smart DNR™ 3D digital noise reduction	0-11
Wide dynamic range (WDR)	True WDR (WDR) Off, WDR2x, WDR3x
Wide dynamic range (WDR) dB	120dB
Privacy zone	16 programmable privacy masks
Alarm notifications	Notifications via e-mail, FTP server or SD card recording
NETWORK	
LAN	802.3 compliance 10/100 LAN
Video compression type	H.264, MJPEG
Resolution	H.264: 1440p/1080p/720p/VGA/D1/CIF MJPEG: 1280x720/800x600/VGA/768x432/D1/CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps - 10Mbps, multi-rate for preview and recording
Bitrate control	Multi streaming CBR/VBR at H.264 (Controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
Ip	IPv4
Protocol	Zero config (Auto IP), ONVIF, TCP/IP, UDP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2c/v3 (MIB-2)
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
Maximum user access	5 users
ONVIF conformance	Yes
Web viewer	OS: Windows®, Mac® OS, Linux® Browser: Internet Explorer®, Google Chrome®, Mozilla Firefox®, Safari®
Video management software	DW Spectrum® IPVMS
Number of DW Spectrum® IPVMS licenses included	1 DW Spectrum® license
Local server recording	DWC-MV84WiAC2: 256GB local memory for recording DWC-MV84WiAC1: 128GB local memory for recording DWC-MV84WiAC6: 64GB local memory for recording
Max. number of CaaS™ cameras in the same network/system	Up to 30 MEGApix® CaaS™ cameras in the same network/system
ENVIRONMENTAL	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	10-90% RH (non-condensing)
IP rating	IP66-rated
IK rating	IK10-rated impact-resistant
Other certifications	CE, FCC, RoHS, UL listed
ELECTRICAL	
Power requirement	DC12V, PoE (IEEE 802.3af Class 3). Adaptor not included.
Power consumption	DC12V: Max 7.1W PoE: Max 9.2W
MECHANICAL	
Material	aluminum vandal housing, polycarbonate dome
Dimensions	4.9" x 3.6" (125 x 92 mm)
Weight	1.87 lb (0.85kg)
Warranty	5 year warranty

Summary

MEGApix® CaaS™ all-in-one series of IP cameras combine the cameras with the ease and power of DW Spectrum® IPVMS and on-board storage. DW Spectrum® IPVMS server is pre-installed and licensed. No additional server hardware is required.

The 4MP IP66-rated, IK-10 impact-resistant low-profile vandal housing features CleanView™ self-cleaning dome treatment. Combine the CaaS™ solution with the DW® Blackjack® NAS device for long-term storage needs.

Features

- All-in-one cameras, no server required
- 4MP 1/3" image sensor at real-time 30fps
- 2.8-12mm vari-focal p-iris lens with motorized zoom and auto-focus
- Built-in 256/128/64GB storage options for up to 30 days retained video
- Easily to deploy with pre-loaded DW Spectrum® IPVMS for out-of-the-box operation
- 24/7 access to live and recorded video feed
- Automatic installation and licensing with first power on
- Connect up to 30 MEGApix® CaaS™ edge cameras
- True Wide Dynamic Range (WDR)
- Dual recording option with Blackjack® NAS appliance
- Dual codecs (H.264, MJPEG) with simultaneous dual-stream
- 100' Smart IR™ with intelligent camera sync
- CleanView™ hydrophobic dome coating repels water, dust and grease
- Ultra low-profile outdoor vandal dome
- Smart DNR™ 3D digital noise reduction
- True day/night with mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Auto white balance (AWB)
- Motion detection
- Web server built-in
- PoE class 3 and DC12V
- Waterproof cabling
- UL listed
- ONVIF conformant, profile S
- IP66 environmental-rated dust-tight and water-resistant
- IK 10-rated impact-resistant
- 5 year warranty



Accessories (Optional)

- 

DWC-VFZW
Wall mount bracket
- 

DWC-VFZJUN
Junction box
- 

DWC-VFZCM
Ceiling mount bracket

☎ : 866.446.3595

✉ : sales@dwcc.tv

🌐 : www.digital-watchdog.com

