

GSM Antennas

GSM-ANT



GSM-ANT3dB



Honeywell offers remote antennas designed to increase GSM signal transmission capability. These durable, low-profile antennas are designed to allow flexible integration with GSM communication devices.

The GSM-ANT Indoor Fixed Length Antenna is designed for indoor use. It comes with 10ft. of RG-174 cable and mounting hardware for ease of installation.

The GSM-ANT3dB Weatherproof Remote Antenna optimizes transmissions with field diversity technology. The versatile, weatherproof design is suitable for indoor or outdoor applications.

SPECIFICATIONS

Electrical

GSM-ANT

- Frequency Range:
 - 824-896 MHz
 - 1850-1990 MHz
- Average Gain: 1dBi
- Maximum power: 10W
- Nominal impedance: 50 ohms
- Pattern: Omni Directional
- Termination: SMA Male

* For Indoor Use Only

GSM-ANT3dB

- Frequency Range:
 - 821-896 MHz
 - 1850-1990 MHz
- Average Gain: 3dBi
- Maximum power: 100W
- Nominal impedance: 50 ohms
- Pattern: Omni Directional
- Termination: N Female
- Operating Temperature: -40° to 185° F (-40° C to 85° C)

* Fully Weatherproof for Outdoor Application

ORDERING

GSM-ANT

Fixed Length Antenna

GSM-ANT3DB

Weatherproof Remote Antenna

GSM3DBKT

Includes **GSM-ANT3DB** antenna and **WA7626-CA SMA** to N adaptor cable

GSM3DB25KT

Includes **GSM-ANT3DB** antenna, **WA7626-CA SMA** to N adaptor cable, 25 ft coax cable

GSM3DB50KT

Includes **GSM-ANT3DB** antenna, **WA7626-CA SMA** to N adaptor cable, 50 ft.coax cable

Honeywell Security & Custom Electronics

Honeywell
2 Corporate Center Drive
Melville, NY 11747
Tel: 800.467.5875
www.honeywell.com