



HX40M 4K HDMI Extender

Commercial-Grade



One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



Commercial-Grade

With durable construction and ultra-sleek design, CE Labs extenders are perfect for any project that requires 24/7 performance.



CE PROLink™

CE Labs PROLink™ Series creates a fully connected PROAV ecosystem. Easily connect, control, and manage your entire network.



3 Year Warranty

CE Labs products are built for professionals. All products come with a 3-year warranty and superior customer support.

PRODUCT OVERVIEW

The HX40M is reliable by design. With commercial-grade performance, the HX40M support 1080p at 40 meters (132 ft). With a rugged chassis the HX40M is ideal for professional environments that require 24/7 performance.

The CE Pro-link™ of HDMI extender kits are the latest generation of reliable HDBaseT extenders for HD/4K/UHD AV signals. The CE Pro-link™ series includes HD and UHD models with a variety of powering and extension distance options. Perfect for AV professionals that demand the most cost effective and installation-friendly features.

FEATURES

Compact Design and rugged steel chassis

Most cost Effective HDBaseT solution

75% lower power consumption

SPECIFICATIONS

MODEL: HX40M

FEATURES

- Uses only one Cat5e/6/7 cable
- Transmission range up to 40M by CAT5e/6/6a/7
- 3D ready and 4K2K capable
- Uncompressed HD video up to 1080p@60Hz@48bits, 4K/30 capable
- Built in EDID auto backup function, EDID Settings
- HDMI and HDCP Compliance
- RoHs, CE, FCC Compliant
- Cat Cable 5e/6/6a/7 Distance: Min. 10 ft (3M) - Max. 132 ft (40M)
- HDMI Cable Type A Distance: Min. 2 ft - Max. 16 ft
- Max. Data Rate 3.4 Gbps
- Audio Transmission Full pass-through

VIDEO

- HDMI 1.3
- HDCP compliance
- Maximum Resolution: 480i/p, 720p, 1080i/P @ 24/50/60Hz
- Max. Distance: 1080i/720p - 230 ft (70M)
- Max. Distance: 1080P - 132 ft (40M)

AUDIO

- Audio support up to LPCM7.1, Dolby TrueHD, DTS-HD MA
- Audio transmission full pass-through

EDID Setup

- OFF, OFF 1080i/LPCM 2 Channel
- OFF, ON 1080p/LPCM 5.1 Channel
- ON, X Learn EDID

POWER

- Wall transformer: 5VDC/ 1A, 2.5 mm connector
- TX Max current: 420mA Power: 0.8-2.4 W
- RX Max current: 180mA Power: 0.8-1 W

IR

- IR Carrier Frequency: 30 - 60Khz
- IR Angle: Transmitter $\pm 30^\circ$
- IR Angle: Receiver $\pm 55^\circ$
- IR Distance: 5m / Bi-directional
- 3.5mm Stereo female phone jack

I/O PORTS

- Transmitter/Receiver HDMI type A
- RJ45 Data Connector
- 2.5mm X 5.5mm female connector Power jack
- LED Indicators: Pwr On = Blue, Link = Green, Activity = Yellow

RJ45 Define: Video Link (TIA/EIA-568-B)

1. Orange-White: TMDS DATA 2 +
2. Orange: TMDS DATA 2+
3. Green-White: TMDS DATA 2+ATA 1 +
4. Blue: TMDS DATA 2+DATA 2 +
5. Blue-White: TMDS 1 -
6. Green: TMDS CLOCK -/ HDMI OV
7. Brown-White: TMDS DATA 2+
8. Brown: TMDS DATA 0-

ACCESSORIES

- 1 IR Transmitter, 1 IR Receiver
- 2 Power wall adapters
- Set of 4 Plastic Drywall Anchors
- Product Manual

MISCELLANEOUS

- Transmitter Dims.: (H) 1", (W) 4", (D) 2.6" | Weight 5.3oz.
- Receiver Dims.: (H) 1", (W) 3.6", (D) 2.6" | Weight 5oz.
- Operating Temp & Humidity 0-55C, 95% Max Rel. Humidity
- Rugged (Industrial) Powder Coated Aluminum Chassis

WARRANTY: *3 year warranty, parts and labor.

Learn more about CE Labs at www.celabs.com.

United States
1-800-767-6189
sales@celabs.com

CE Labs, LLC reserves the right to change or update without notice. CE Labs, the CE Labs logo and CESync are registered trademarks of CE Labs, LLC. All other trademarks are the property of their respective owner. 2021 CE Labs, LLC. All rights reserved.

