




Product Image	
Part number	909020114 – PAC OneProx™ GS3 MT PIN & Prox
Dimensions	W 89 x H 115 x D 30mm
Weight	300g
RFid Frequency	Low Frequency (125kHz and 153.6kHz) and High Frequency (13.56MHz)
PAC ID Devices	PAC, KeyPAC, Stanley, PAC Ops™ Lite, PAC Ops™
Programmable Output Formats	PAC, PAC64 and Wiegand
Maximum Read Range	up to 100mm
Intruder Grading	Security Grade 3
Environment	IP65 – Indoor/Outdoor weather resistant
Power	12 – 24V DC, <90 mAmp @ 12V DC
Operating Temperature	-40 to 66 oC
Operating Humidity	10-85% Relative humidity
Audio/Visual Indicators	Audible Sounder and Red/Green LEDs
Tamper Output	Yes, certified to EN 50131-1 and EN 50131-3
Recommended Cabling	PAC output - 6 core 24 AWG alarm cable (unscreened) Wiegand output – 5 core 22 AWG cable
Material	UL rated Polycarbonate
Certification	CE compliant
Warranty	Lifetime against electronic failure

**Date of print/release: (September 2020)**

This document is provided by STANLEY Security or its affiliates ("STANLEY") for general information purposes only. STANLEY warrant the accuracy of the data as at the date of print/release, but it may be subject to change after such date. STANLEY will not be responsible for any loss or damage that may arise from reliance thereof. Copyright © STANLEY Security 2020. PAC, GDx and 3xLOGIC are the trade marks of STANLEY Security, Stanley Black & Decker, Inc., or their affiliates.

Ordering Information:

PAC Access Control, 1 Park Gate Close,
Bredbury, Stockport, Cheshire, SK6 2SZ
customerservices@pacgdx.com | +44 (0) 161 406 3400
www.pacgdx.com