

Product Highlights

Flexibility and Reliability

A combination of RJ-45, SFP, and SFP+ ports provides the necessary flexibility to adapt to a wide range of applications and environments

Security and Authentication Features

Robust security features, including the D-Link Safeguard Engine™, protect against malicious attacks, while authentication tools allow access control

High Bandwidth

Up to four 10G SFP+ ports¹ provide maximum throughput, reduce latency, and provide bandwidth for future network expansion



DGS-1210ME Series

Metro Ethernet Switches

Features

Flexible Hardware Design

- Available in multiple configurations:
 - Gigabit Ethernet with 1G SFP ports
 - 8/16/24/48 10/100/1000BASE-T ports
 - 8/24/48 10/100/1000BASE-T PoE ports
 - 2 or 4 1G SFP ports
 - Gigabit Ethernet with 10G SFP+ ports
 - 24 10/100/1000BASE-T ports
 - 24 100/1000 Mbps SFP ports
 - 4 10G SFP+ ports
 - Gigabit Ethernet SFP and 1000BASE-T ports
 - 10 1G SFP and 2 10/100/1000BASE-T ports
- Designed for standard 1U rack-mounting
- Surge protection on all Gigabit Ethernet ports²

Layer 2 Features

- 16K MAC address table
- IEEE 802.1D STP, 802.1w RSTP, and 802.1s MSTP
- Loopback detection
- Supports IEEE 802.3ad Link Aggregation
- Port-based Q-in-Q
- VLAN Trunking

Security/Authentication

- Port security
- SSH/SSL
- IP-MAC-Port Binding (IMPB)
- Access Control List (ACL) and IEEE 802.1X
- Guest VLAN

The DGS-1210ME Series Metro Ethernet Switches are a range of switches designed for Metro Ethernet applications. They feature a variety of port configurations, including 10/100/1000BASE-T RJ-45 ports, 1G SFP ports, and 10G SFP+ ports for increased network bandwidth. Surge protection, advanced Layer 2 functions, and a suite of security and management tools make the DGS-1210ME Series Metro Ethernet Switches ideal for Metro Ethernet applications.

Multi-Gigabit Performance

The DGS-1210ME Series Metro Ethernet Switches come in a variety of port setups, including Gigabit Ethernet RJ-45, 1G Ethernet SFP ports, or 10G SFP+ ports. All models offer a minimum of at least two 1G Ethernet SFP ports, excluding the DGS-1210-12TS/ME which offers ten 1G SFP ports and two 10/100/1000BASE-T ports. The DGS-1210-28X/ME and DGS-1210-28XS/ME offer four 10G SFP+ ports for improved uplink bandwidth. The DGS-1210-10P/ME, DGS-1210-28P/ME, DGS-1210-52P/ME, and DGS-1210-52MP/ME switches feature Power over Ethernet (PoE), allowing compatible devices to be installed and powered in remote locations without immediate access to power outlets.

Efficient and Resilient

For mission critical environments, the DGS-1210ME Series Metro Ethernet Switches support IEEE 802.1D 2004 edition, 802.1w, and 802.1s Spanning Tree Protocols (STP). The Spanning Tree Protocol allows the switches to participate in Spanning Tree topology, providing an alternative Layer 2 path in the event of a network failover. The switches also support IEEE 802.3ad link aggregation, which enables multiple ports to be grouped to form a single virtual port, increasing bandwidth and redundancy for higher availability. This series furthermore features IEEE 802.1p Quality of Service (QoS), allowing for real-time traffic classification into Weighted Round Robin (WRR) and strict priority levels mapped to 8 queues. Advanced traffic classification parameters allow the network to be tuned for flexible configurations for specific multimedia applications such as VoIP or IPTV.

Security & Authentication

The DGS-1210ME Series supports IEEE 802.1X port-based/host-based access control, guest VLAN, and RADIUS/TACACS+ authentication for strict access control to the network. The IP-MAC-Port Binding (IMPB) feature allows administrators to associate a source IP address with a designated MAC address and also offers the flexibility to define the port number to enhance user access control. The built-in D-Link Safeguard Engine™ protects the CPU from broadcast, multicast, and unicast flooding by automatically trapping packets and logging events in these situations. In addition, the Access Control List (ACL) feature enhances network security and switch performance.

Management Capabilities

A user-friendly web interface gives administrators access to advanced management features such as DHCP auto-configuration. This enables switches to load their configuration from a TFTP server once they have been assigned an IP address, allowing central management of device configurations. The switches support Link Layer Discovery Protocol (LLDP), which advertises the device's capabilities and identity to the local network, allowing administrators to better manage their network topology. Each port also supports cable diagnostics, which can be used to troubleshoot cable length and functionality problems remotely, resulting in lower management overheads.

Traffic & Bandwidth Control

Integrated bandwidth control allows network administrators to define the throughput levels for ingress and egress bandwidth. It provides a minimum granularity of 64 Kbps for ingress port and flow-based bandwidth control, and a minimum granularity of 64 Kbps for egress queue bandwidth. The DGS-1210ME Series also supports traffic control, which optimizes performance by dropping packets when exceeding a set threshold, while port mirroring helps administrators facilitate traffic diagnostics and track network performance. The DGS-1210ME Series also provides IGMP snooping with IGMP authentication to prune multicast traffic and to optimize available bandwidth.

Multicast Applications

The DGS-1210ME Series features a full set of L2 multicast functions, including IGMP snooping, IGMP filtering, fast leave, and multicast traffic configuration for specific ports. With L2 multicast support, the DGS-1210ME Series is ready and capable of handling growing IPTV applications. Host-based IGMP/MLD snooping allows for multiple multicast subscribers per physical interface, and ISM VLAN sends multicast streams in a multicast VLAN, saving bandwidth on the backbone. ISM VLAN profiles allow users to bind or replace the predefined multicast registration information to subscriber ports quickly and easily.



DGS-1210-10/ME



DGS-1210-10P/ME



DGS-1210-20/ME



DGS-1210-12TS/ME



DGS-1210-28P/ME



DGS-1210-28X/ME



DGS-1210-28/ME v.A1



DGS-1210-28XS/ME



DGS-1210-52MP/ME



DGS-1210-52P/ME



DGS-1210-52/ME



DGS-1210-28/ME v.B1

Technical Specifications				
Model Number	DGS-1210-10P/ME	DGS-1210-28P/ME	DGS-1210-52MP/ME	DGS-1210-52P/ME
Hardware Version	A1	A1	A1	A1
Interface				
Size	<ul style="list-style-type: none"> • 11-inch standard rack-mount width • 1U Height 	<ul style="list-style-type: none"> • 19-inch standard rack-mount width • 1U Height 	<ul style="list-style-type: none"> • 19-inch standard rack-mount width • 1U Height 	<ul style="list-style-type: none"> • 19-inch standard rack-mount width • 1U Height
Interfaces	<ul style="list-style-type: none"> • 8 10/100/1000BASE-T PoE • 2 1G SFP 	<ul style="list-style-type: none"> • 24 10/100/1000BASE-T PoE • 4 1G SFP 	<ul style="list-style-type: none"> • 48 10/100/1000BASE-T PoE • 4 1G SFP 	<ul style="list-style-type: none"> • 24 10/100/1000BASE-T PoE • 24 10/100/1000BASE-T • 4 1G SFP
Port Standards & Functions	<ul style="list-style-type: none"> • Ports 1 to 8 compliant with IEEE 802.3at 	<ul style="list-style-type: none"> • Ports 1 to 4 compliant with IEEE 802.3at • Ports 5 to 24 compliant with IEEE 802.3af 	<ul style="list-style-type: none"> • Ports 1 to 8 compliant with IEEE 802.3at • Ports 9 to 48 compliant with IEEE 802.3af 	<ul style="list-style-type: none"> • Ports 1 to 8 compliant with IEEE 802.3at • Ports 9 to 24 compliant with IEEE 802.3af
Console Port	<ul style="list-style-type: none"> • RJ-45 console port 			
Other Port Standards & Functions	<ul style="list-style-type: none"> • IEEE 802.3 10BASE-T Ethernet (twisted-pair copper) • IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper) • IEEE 802.3ab 1000BASE-T Gigabit Ethernet (twisted-pair copper) <ul style="list-style-type: none"> • IEEE 802.3az compliance <ul style="list-style-type: none"> • Auto-negotiation • IEEE 802.3x Flow Control • IEEE 802.3z 1000BASE-X Gigabit Fiber 			
Network Cables	<ul style="list-style-type: none"> • UTP Cat. 5, Cat. 5e (100 m max.) 			
Full/Half-Duplex	<ul style="list-style-type: none"> • Full/half-duplex for 10/100 Mbps speeds • Full-duplex for 1000 Mbps speed 			
Media Interface Exchange	<ul style="list-style-type: none"> • Auto MDI/MDIX adjustment for all twisted-pair ports 			
Performance				
Switching Capacity	40 Gbps	56 Gbps	104 Gbps	104 Gbps
Forwarding Method	Store-and-forward			
MAC Address Table Size	16K entries			
MAC Address Update	Up to 256 static MAC entries			
64-byte Max. Forwarding Rate	14.88 Mpps	41.7 Mpps	77.4 Mpps	77.4 Mpps
CPU Memory	128 MB DDR3			
Packet Buffer	1.5 MB	1.5 MB	3.0 MB	3.0 MB
Flash Memory	32 MB			
LEDs				
Power (per device)	✓	✓	✓	✓
Console (per device)	✓	✓	✓	✓
Link/Active/Speed (per port)	✓	✓	✓	✓
Fan Error		✓	✓	✓

Physical/Environmental				
MTBF	309,439 hours	239,534 hours	257,252 hours	201,071 hours
Acoustic	0 dB(A)	52.4 dB(A)	50.1 dB(A)	47.3 dB(A)
Heat Dissipation	347 BTU/hr	840.89 BTU/hr	1648.23 BTU/hr	912.96 BTU/hr
Power Input	AC Input: 100 to 240 V AC, 50/60 Hz			
Maximum Power Consumption	103.4 W (PoE on) 103.4 W (PoE off)	246.5 W (PoE on) 28.4 W (PoE off)	483.1 W (PoE on) 48.9 W (PoE off)	270.2 W (PoE on) 47 W (PoE off)
Maximum PoE Budget	78 W	193 W	370 W	193 W
Standby Power Consumption	10.3 W/100 V 11.1 W/240 V	24.5 W/100 V 21.9 W/240 V	29.6 W/100 V 28.2 W/240 V	29.5 W/100 V 27.5 W/240 V
Dimensions (W x D x H)	280 x 180 x 44 mm	440 x 210 x 44 mm	440 x 430 x 44 mm	440 x 430 x 44 mm
Ventilation	Fanless	2 x Smart fans	3 x Smart fans	2 x Smart fans
Power Surge Protection	All Gigabit Ethernet ports support IEC 61000-4-5 surge protection			
Operating Temperature	-5 to 50 °C (23 to 122 °F)			
Storage Temperature	-40 to 70 °C (-40 to 158 °F)			
Operating Humidity	10% to 90% non-condensing			
Storage Humidity	5% to 90% non-condensing			
EMI	FCC class A, CE class A, VCCI			
Safety Certifications	CE, LVD, UL, CB			

Technical Specifications					
Model Number	DGS-1210-10/ME	DGS-1210-20/ME	DGS-1210-28/ME	DGS-1210-28/ME	DGS-1210-52/ME
Hardware Version	A1	A1	A1	B1	A1
Interface					
Size	• 11-inch standard rack-mount width • 1U Height	• 11-inch standard rack-mount width • 1U Height	• 19-inch standard rack-mount width • 1U Height	• 19-inch standard rack-mount width • 1U Height	• 19-inch standard rack-mount width • 1U Height
Interfaces	• 8 10/100/1000BASE-T • 2 1G SFP	• 16 10/100/1000BASE-T • 4 1G SFP	• 24 10/100/1000BASE-T • 4 1G SFP	• 24 10/100/1000BASE-T • 4 1G SFP	• 48 10/100/1000BASE-T • 4 1G SFP
Console Port	RJ-45 console port				
Other Port Standards & Functions	<ul style="list-style-type: none"> • IEEE 802.3 10BASE-T Ethernet (twisted-pair copper) • IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper) • IEEE 802.3ab 1000BASE-T Gigabit Ethernet (twisted-pair copper) <ul style="list-style-type: none"> • IEEE 802.3az compliance <ul style="list-style-type: none"> • Auto-negotiation • IEEE 802.3x Flow Control • IEEE 802.3z 1000BASE-X Gigabit Fiber 				
Network Cables	• UTP Cat. 5, Cat. 5e (100 m max.)				
Full/Half-Duplex	<ul style="list-style-type: none"> • Full/half-duplex for 10/100 Mbps speeds • Full-duplex for 1000 Mbps speed 				
Media Interface Exchange	• Auto MDI/MDIX adjustment for all twisted-pair ports				

Performance					
Switching Capacity	20 Gbps	40 Gbps	56 Gbps	56 Gbps	104 Gbps
64-byte Max. Forwarding Rate	14.88 Mpps	29.80 Mpps	41.7 Mpps	41.7 Mpps	77.4 Mpps
MAC Address Table Size	16K entries				
CPU Memory	128 MB DDR3				
Packet Buffer	1.5 MB	1.5 MB	1.5 MB	1.5 MB	3.0 MB
Flash Memory	32 MB				
LEDs					
Power (per device)	✓	✓	✓	✓	✓
Console (per device)	✓	✓	✓	✓	✓
Link/Active/Speed (per port)	✓	✓	✓	✓	✓
Fan Error					✓
Physical/Environmental					
MTBF	309,072 hours	392,728 hours	388,138 hours	497,918 hours	334,101 hours
Acoustic	0 dB(A)	0 dB(A)	0 dB(A)	0 dB(A)	49.7 dB(A)
Heat Dissipation	46.35 BTU/hr	54.91 BTU/hr	76.59 BTU/hr	60.12 BTU/hr	130.58 BTU/hr
Power Input	AC Input: 100 to 240 V AC, 50/60 Hz				
Optional 54 W AC to DC PSU				<ul style="list-style-type: none"> • Output: 12.4 V/3.7 A (min 11.78 V & max 13.02 V); 13.6 V/0.6 A (min 13.40 V & max 13.80 V) • Charging output for lead-acid battery: 13.6 V +/- 1.5%; charge current 0.6 A +/- 0.1 A 	
Battery Connection Input				<ul style="list-style-type: none"> • Rear RPS socket for connecting external lead-acid batteries • Battery status monitoring through CLI or SNMP 	
Maximum Power Consumption	13.59 W 9.40 W (Standby)	16.09 W 8.80 W (Standby)	22.45 W 17.84 W (Standby)	17.62 W 8.86 W (Standby)	38.27 W 29.49 W (Standby)
Dimensions (W x D x H)	280 x 126 x 44 mm	280 x 180 x 44 mm	440 x 140 x 44 mm	440 x 140 x 44 mm	440 x 210 x 44 mm
Ventilation	Fanless	Fanless	Fanless	Fanless	1 x Smart fan
Power Surge Protection	All Gigabit Ethernet ports support IEC 61000-4-5 surge protection				
Operating Temperature	-5 to 50 °C (23 to 122 °F)				
Storage Temperature	-40 to 70 °C (-40 to 158 °F)				
Operating Humidity	10% to 90% non-condensing				
Storage Humidity	5% to 90% non-condensing				

EMI	FCC class A, CE class A, VCCI
Safety Certifications	CE, LVD, UL, CB

Technical Specifications

Model Number	DGS-1210-12TS/ME	DGS-1210-28X/ME	DGS-1210-28XS/ME
Hardware Version	B1	B1	B1
Interface			
Size	<ul style="list-style-type: none"> • 11-inch standard rack-mount width • 1U Height 	<ul style="list-style-type: none"> • 19-inch standard rack-mount width • 1U Height 	<ul style="list-style-type: none"> • 19-inch standard rack-mount width • 1U Height
Interfaces	<ul style="list-style-type: none"> • 10 1G SFP • 2 10/100/1000BASE-T 	<ul style="list-style-type: none"> • 24 10/100/1000BASE-T • 4 10G SFP+ 	<ul style="list-style-type: none"> • 24 100/1000 Mbps SFP • 4 10G SFP+
Console Port	RJ-45 console port		
Other Port Standards & Functions	<ul style="list-style-type: none"> • IEEE 802.3 10BASE-T Ethernet (twisted-pair copper) • IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper) • IEEE 802.3ab 1000BASE-T Gigabit Ethernet (twisted-pair copper) <ul style="list-style-type: none"> • IEEE 802.3az compliance <ul style="list-style-type: none"> • Auto-negotiation • IEEE 802.3x Flow Control • IEEE 802.3ae 10 Gigabit Ethernet (for 28X/ME, 28XS/ME) <ul style="list-style-type: none"> • IEEE 802.3u 100BASE-FX (for 28XS/ME) • IEEE 802.3z 1000BASE-X Gigabit Fiber (for 28XS/ME, 12TS/ME) 		
Network Cables	<ul style="list-style-type: none"> • UTP Cat. 5, Cat. 5e (100 m max.) 		
Full/Half-Duplex	<ul style="list-style-type: none"> • Full/half-duplex for 10/100 Mbps speeds • Full-duplex for 1000 Mbps and 10G Mbps speeds 		
Media Interface Exchange	<ul style="list-style-type: none"> • Auto MDI/MDIX adjustment for all twisted-pair ports 		
Performance			
Switching Capacity	24 Gbps	128 Gbps	128 Gbps
64-byte Max. Forwarding Rate	17.86 Mpps	95.24 Mpps	95.24 Mpps
MAC Address Table Size	16K Entries		
CPU Memory	256 MB DDR3		
Packet Buffer	1.5 MB	1.5 MB	1.5 MB
Flash Memory	32 MB		
LEDs			
Power (per device)	✓	✓	✓
Console (per device)	✓	✓	✓
Link/Active/Speed (per port)	✓	✓	✓
Fan Error		✓	✓
Physical/Environmental			
MTBF	405,083 hours	450,021 hours	243,327 hours
Acoustic	0 dB(A)	42.5 dB(A)	48.9 dB(A)

Heat Dissipation	47.25 BTU/hr	83.72 BTU/hr	115.17 BTU/hr
Power Input	AC Input: 100 to 240 V AC, 50/60 Hz		
Maximum Power Consumption	13.85 W 7.49 W (Standby)	24.5 W 13 W (Standby)	33.4 W 16.7 W (Standby)
Dimensions (W x D x H)	280 x 180 x 44 mm	440 x 210 x 44 mm	440 x 210 x 44 mm
Ventilation	Fanless	1 x Smart fan	2 x Smart fans
Power Surge Protection	All Gigabit Ethernet ports support IEC 61000-4-5 surge protection		
Operating Temperature	-5 to 50 °C (23 to 122 °F)		
Storage Temperature	-20 to 70 °C (-4 to 158 °F)		
Operating Humidity	0% to 95% RH		
Storage Humidity	0% to 95% RH		
EMI	BSMI, CE, FCC, VCCI	CE	
Safety Certifications	UL, CB, LVD, BSMI	CB, LVD	

Software

L2 Features	<ul style="list-style-type: none"> • MAC address table: 16K entries • Spanning Tree Protocols <ul style="list-style-type: none"> - 802.1D STP - 802.1w RSTP - 802.1s MSTP - BPDU filtering - Root restriction • Loopback detection 	<ul style="list-style-type: none"> • Mirroring <ul style="list-style-type: none"> - Support 1 mirroring group - Support One-to-One, Many-to-One, Flow-based (ACL) mirroring for ingress traffic • L2 Protocol Tunneling (L2PT) • Link aggregation <ul style="list-style-type: none"> - Compliant with 802.3ad - Supports max 8 groups, 8 ports per group
L2 Multicasting	<ul style="list-style-type: none"> • IGMP Snooping <ul style="list-style-type: none"> - IGMP v1/v2 snooping, v3 awareness - IGMP authentication/filtering - Supports 256 groups - VLAN/host-based IGMP snooping fast leave - Report suppression 	<ul style="list-style-type: none"> • MLD Snooping <ul style="list-style-type: none"> - MLD v1, MLD v2 awareness - Supports 256 groups
VLAN	<ul style="list-style-type: none"> • 802.1Q tagged VLAN • VLAN group • Max. 4094 VLAN groups • Port-based VLAN • GVRP • Asymmetric VLAN 	<ul style="list-style-type: none"> • Max. 256 dynamic VLAN • 802.1v protocol VLAN • VLAN trunking • MAC-based VLAN • Port-based Q-in-Q • ISM VLAN
L3 Features	<ul style="list-style-type: none"> • Max. 256 ARP entries • Supports 255 static ARP entries 	<ul style="list-style-type: none"> • Supports Gratuitous ARP
Quality of Service (QoS)	<ul style="list-style-type: none"> • CoS based on: <ul style="list-style-type: none"> - Switch port - 802.1p priority queues - VLAN ID - MAC address - IPv4/IPv6 address - DSCP - TOS - Protocol type - TCP/UDP port - IPv6 traffic class 	<ul style="list-style-type: none"> • Bandwidth control <ul style="list-style-type: none"> - Port-based (Ingress, Min. Granularity 64 Kbps) - Flow-based (Ingress, Min. Granularity 64 Kbps) - Egress queue bandwidth control (Min. Granularity 64 Kbps) • Queue Handling <ul style="list-style-type: none"> - Strict priority - Weighted Round Robin (WRR) • 8 outbound queues

Access Control List (ACL)	<ul style="list-style-type: none"> • ACL based on <ul style="list-style-type: none"> - Switch port - 802.1p priority - VLAN ID - MAC address - EtherType - TOS - IPv4/v6 address - DSCP - Protocol type - IPv4/IPv6 TCP/UDP port number - ICMP - IPv6 traffic class 	<ul style="list-style-type: none"> • Up to 256 ingress access rules • ACL Action (permit/deny/mirror) • Time-based ACL • ACL statistics • CPU interface filtering
AAA	<ul style="list-style-type: none"> • 802.1X <ul style="list-style-type: none"> - Host-based access control - Port-based access control • Guest VLAN 	<ul style="list-style-type: none"> • RADIUS accounting • TACACS+ accounting • User Account Privilege (4 level user access)
Security	<ul style="list-style-type: none"> • SSH v2 • SSL v1/2/3 • Port security (Up to 64 MAC addresses per port) • IP-MAC-Port Binding (IMPB) <ul style="list-style-type: none"> - ARP inspection - IP inspection - IPv6 DHCP snooping • Broadcast/Multicast/Unicast storm control 	<ul style="list-style-type: none"> • D-Link Safeguard Engine • DHCP server screening • DHCP client filtering • ARP spoofing prevention • BPDU attack protection • DoS attack prevention • Traffic segmentation
OAM	<ul style="list-style-type: none"> • 802.3ah Ethernet Link OAM <ul style="list-style-type: none"> - Support 802.3ah link layer remote loopback and discovery (System log and SNMP) - 802.3ah D-Link extension: D-link Unidirectional Link Detection (DULD), (System log and SNMP) 	<ul style="list-style-type: none"> • Cable diagnostics
Management	<ul style="list-style-type: none"> • Web-based GUI (IPv4/IPv6) • Command Line Interface (CLI) • Telnet Server/Client (Support IPv4/IPv6) • TFTP client (IPv4/IPv6) • Command logging • SNMP v1/v2c/v3 • SNMP traps • System log • RMON v1 • RMON v2 • LLDP • BootP/DHCP client • DHCP auto-configuration • Text-editable config file • Trusted host 	<ul style="list-style-type: none"> • DHCP relay (IPv4/IPv6) <ul style="list-style-type: none"> - DHCP relay agent/local relay - DHCP relay option 12, 37, 38 - DHCP relay option 82 • PPPoE Circuit-ID tag insertion • Trap/alarm/log severity control • CPU monitoring • SNTp • LLDP • Debug command • Password recovery • Password encryption • Backdoor password • Trusted host
MIB	<ul style="list-style-type: none"> • RFC1213 MIB II • RFC1493 Bridge MIB • RFC1907 SNMPv2 MIB • RFC1757, 2819 RMON MIB • RFC2021 RMONv2 MIB • RFC1398, 1643, 1650, 2358, 2665 Ether-like MIB • RFC2674,4363 802.1p MIB 	<ul style="list-style-type: none"> • RFC 2233, 2863 IF MIB • RFC 2618 RADIUS authentication client MIB • RFC 2620 RADIUS accounting client MIB • RFC 2925 ping & traceroute MIB • Private MIB • D-Link Zone Defense MIB
IETF Standard	<ul style="list-style-type: none"> • RFC768 UDP • RFC791 IP • RFC792 ICMPv4 • RFC2463, 4443 ICMPv6 • RFC793 TCP • RFC826 ARP 	<ul style="list-style-type: none"> • RFC 2474, 3260 definition of the DS Field in the IPv4 and IPv6 header • RFC 1321, 2284,2865, 3580, 3748 Extensible Authentication Protocol (EAP) • RFC2571, RFC2572, RFC2573, RFC2574 SNMP
IPv6	<ul style="list-style-type: none"> • RFC1981 Path MTU Discovery • RFC2460 IPv6 • RFC2461, 4861 Neighbor Discovery • RFC2462, 4862 IPv6 Stateless Address Auto-configuration 	<ul style="list-style-type: none"> • RFC2464 IPv6 Neighbor over Ethernet and definition • RFC3513, 4291 IPv6 addressing architecture • RFC2893, 4213 IPv4/IPv6 dual stack function

Order Information	
Part Number	Description
DGS-1210-10/ME	8 10/100/1000BASE-T + 2 1000BASE-T SFP Ports L2 Management Switch
DGS-1210-20/ME	16 10/100/1000BASE-T + 4 1000BASE-T SFP Ports L2 Management Switch
DGS-1210-28/ME (v.A1, v.B1)	24 10/100/1000BASE-T + 4 1000BASE-T SFP Ports L2 Management Switch
DGS-1210-52/ME	48 10/100/1000BASE-T + 4 1000BASE-T SFP Ports L2 Management Switch
DGS-1210-28P/ME	24 10/100/1000BASE-T PoE + 4 1000BASE-T SFP Ports L2 Management Switch
DGS-1210-10P	8 10/100/1000BASE-T PoE + 2 1000BASE-T SFP Ports L2 Management Switch
DGS-1210-52P	24 10/100/1000 BASE-T PoE + 24 10/100/1000BASE-T + 4 1000BASE-T SFP Ports L2 Management Switch
DGS-1210-52MP	48 10/100/1000BASE-T PoE + 4 1000BASE-T SFP Ports L2 Management Switch
DGS-1210-12TS/ME	10 1000BASE-T SFP + 2 10/100/1000BASE-T Ports L2 Management Switch
DGS-1210-28X/ME	24 10/100/1000BASE-T + 4 10GBASE-T SFP+ Ports L2 Management Switch
DGS-1210-28XS/ME	24 100/1000Mbps SFP + 4 10GBASE-T SFP+ Ports L2 Management Switch
Redundant Power Supply (for DGS-1210-10/ME, 12TS/ME, 28XS/ME, 28X/ME, 28/ME B1 only)	
DPS-200A	Redundant Power Supply DPS-200A
DPS-500A	Redundant Power Supply DPS-500A
DPS-500DC	Redundant Power Supply DPS-500DC
DPS-CB150-2PS	150cm RPS cable for connecting DGS-1210-10/ME, 12TS/ME, 28XS/ME, 28X/ME, and DPS-200A/500A/500DC
SU54-21124-000S	Optional 54 W AC to DC Power Supply Unit with external lead-acid battery support that can be used as a redundant power supply or to connect an external 12 V DC lead-acid battery to charge the switch. The minimum requirement voltage for the lead-acid battery is 12 V DC, with a minimum capacity of 2 AH (for DGS-1210-28/ME B1 only).
Optional SFP Transceivers	
DEM-310GT	1000BASE-LX, Single-mode, 10 km
DEM-311GT	1000BASE-SX, Multi-mode, 500 m
DEM-312GT2	1000BASE-SX, Multi-mode, 2 km
DEM-312GT2	1000BASE-LHX, Single-mode, 50 km
DEM-315GT	1000BASE-ZX, Single-mode, 80 km
DGS-712	1000BASE-T 100 m (only supports 1000 Mbps mode) (no flow control)
DEM-302S-LX	1000BASE-LX, Single-mode, 2 km
DEM-210	100BASE-FX, Single-mode, 15 km (for DGS-1210-28XS/ME only)
DEM-211	100BASE-FX, Multi-mode, 2 km (for DGS-1210-28XS/ME only)
Optional WDM SFP Transceiver	
DEM-330T	1000BASE-LX, Single-mode, 10 km, Tx: 1550, Rx: 1310 nm
DEM-330R	1000BASE-LX, Single-mode, 10 km, Tx: 1310, Rx: 1550 nm
DEM-331T	1000BASE-LX, Single-mode, 40 km, Tx: 1550, Rx: 1310 nm
DEM-331R	1000BASE-LX, Single-mode, 40 km, Tx: 1310, Rx: 1550 nm

DGS-1210ME Series Metro Ethernet Switches

DEM-302S-BXD	1000BASE-LX, Single-Mode, 2 km, Tx: 1550, Rx: 1310 nm
DEM-302S-BXU	1000BASE-LX, Single-Mode, 2 km, Tx: 1310, Rx: 1550 nm
DEM-220T	100BASE-BX, Single-mode, 20 km, Tx: 1550, Rx: 1310 nm (for DGS-1210-28XS/ME only)
DEM-220R	100BASE-BX, Single-mode, 20 km, Tx: 1310, Rx: 1550 nm (for DGS-1210-28XS/ME only)
Optional SFP+ Transceivers (for DGS-1210-28X/ME, 28XS/ME only)	
DEM-431XT	10GBASE-SR SFP+ Transceiver (without DDM), 33 m: OM1 MMF, 82 m: OM2 MMF, 300 m: OM3 MMF
DEM-431XT-DD	10GBASE-SR SFP+ Transceiver (with DDM), 33 m: OM1 MMF, 82 m: OM2 MMF, 300 m: OM3 MMF
DEM-432XT	10GBASE-LR SFP+ Transceiver (without DDM), 10 km
DEM-432XT-DD	10GBASE-LR SFP+ Transceiver (with DDM), 10 km
DEM-433XT	10GBASE-ER SFP+ Transceiver (without DDM), 40 km
DEM-433XT-DD	10GBASE-ER SFP+ Transceiver (with DDM), 40 km
DEM-434XT	10GBASE-ZR SFP+ Transceiver (without DDM), 80 km
DEM-436XT-BXD	10GBASE-LR BiDi SFP+ Transceiver (without DDM), Tx: 1330 nm, Rx: 1270 nm, 20 km
DEM-436XT-BXU	10GBASE-LR BiDi SFP+ Transceiver (without DDM), Tx: 1270 nm, Rx: 1330 nm, 20 km
Optional SFP+ Direct Attach Stacking Cables (for DGS-1210-28X/ME, 28XS/ME only)	
DEM-CB100S	10-GbE SFP+ 1 m Direct Attach Cable
DEM-CB300S	10-GbE SFP+ 3 m Direct Attach Cable
DEM-CB700S	10-GbE SFP+ 7 m Direct Attach Cable

¹ Up to 4 10G SFP+ uplink ports are available in the DGS-1210-28X/ME and DGS-1210-28XS/ME switches.

² All Gigabit Ethernet ports of the DGS-1210ME Series switches support surge protection.

Please note that the latest firmware for the DGS-1210-28/ME B1 (v7.00) is not backwards compatible with A1 hardware.

Updated 07/05/2016