



INTELLIGENT VIDEO DRIVING PROFIT




## 6MP Fisheye Network Dome

The Ax78 6MP provides 4 simultaneous, independently controlled digital pan-tilt-zoom (ePTZ) video streams, which may be recorded or viewed live as well as a built-in microphone and speaker allowing two way communication.

This camera allows viewing video via standard web browser with no software required. Users of SRX-Pro software will be able to view and control all four video streams in SRX-Pro Server, SRX-Pro Remote and Video Pilot Client. Only one IP license is required to support all four video streams.

The Ax78 camera has no moving parts, reducing maintenance costs. This camera comes with the full 360 degree field of view so fewer cameras are required to cover any facility with minimal blind spots. Perfect for both indoor and outdoor installations, the (digital) wide dynamic range function of this camera series helps achieve superb image quality with for even the most challenging environments.

Built-in microphone and speaker allow for the two-way audio communication between the SRX-Pro Server site and the camera installation site, while microSD support allows for 'edge' video recording in case of the network failure.



Mounting Options

\*Mounting hardware sold separately





Image System	
Image Sensor	Progressive Scan CMOS 1/1.8
Optical System	
Focal Length	1.27 mm
F-stop Range (F-number)	F2.8
Horizontal Angle of View	360°
Day/Night	Mechanical ICR
Electric	
Digital Noise Reduction	3D
Wide Dynamic Range (WDR)	Digital WDR
Minimum Illumination	0.05 lux F1.2 (Color mode) 0.3 lux F2.8 (Color mode) 0 lux w/ IR ON (BW mode)
Electric Shutter	NTSC: 1/30~1/100000 sec PAL: 1/25~1/100000 sec
Back Light Compensation (BLC)	Off / On (5 Area Selectable)
On-board (Edge) Storage	1 x microSD/SDHC/SDXC slot up to 64GB. Card sold separately
Audio	
Audio Input	1, built-in microphone (24 dB)
Audio Output	1, built-in speaker (supports echo cancellation)
Audio Format	G.711 A-law/G.711 $\mu$ -law/G.726
Audio In/Out Level	Mic Level

Network Specifications	
Video Streaming and Compression Method	Fisheye Dual Streaming H.264 / MJPEG
Maximum Framerate vs Resolution	6MP (3072x2048)@ 30fps/25fps
Live Mode Options	Mode 1: Fisheye + Panorama + 3PTZ Mode 2: Fisheye OR 4PTZ Mode 3: Fisheye (main + sub stream) + 3PTZ Mode 4: Panorama (main + sub stream)
Network Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP
Security Access	Multiple privilege control with password protection
Users	1 Administrator, 4 Operators/Viewers
Other Features	
Other	Privacy Mask, Edge Motion Detection, Edge Tamper Detection, Edge Intrusion Detection, Edge Line Crossing Detection, Smart IR
Mechanism	
Dimensions (Ø x H)	Ø164mm x 52mm (Ø6 7/16 in x 2 1/16)
Weight	1400g (3.08lb)
Connectors	Network: RJ-45 (PoE supported) Power Input: DC12V (Optional)
IR Distance	15m (49ft)
Power Supply	
Power Requirement	DC12V / PoE (IEEE 802.3af Class 4)
Power Consumption (max.)	12W
Environment	
Operating Temperature	-30°C - 60°C (-22°F - 140°F)
Operating Humidity	95%, non-condensing
Regulations, Ratings	
Regulations, Ratings	FCC Class B, CE, UL, IP66, IK10, ONVIF
Warranty	
Warranty	5 years parts and labor

## RELATED PRODUCTS



**DB60CPM**  
DB60CPM  
Corner/Pole  
Mount Bracket



**DB60**  
DB60  
Wallmount  
Goose Neck  
Bracket



**DB78TSM**  
DB78TSM  
Angle wall/ceiling  
mount kit



**DB78BB**  
DB78BB  
Pendant mount  
Back Box



[www.i3international.com](http://www.i3international.com)  
1.866.840.0004

**Canada Head Office**  
780 Birchmount Rd, Unit 16,  
Toronto, ON M1K 5H4

**i3 America (Nevada) Inc.**  
4001 Cobb International Boulevard,  
Kennesaw, GA 30152