

# PMAX-1003



Flush Mount Kit (for D6x, D7x, D8x, E61~E67, E7x [except E78], E81~E88)

## ► Specifications

### Device


Product Type	Camera Mount
Application Environment	Indoor/Outdoor
Description	Flush Mount Kit (for D6x, D7x, D8x, E61~E67, E7x [except E78], E81~E88)













### General

Weight	305.5g (0.674lb)
Dimensions	(Ø x H): 197.2mm x 72.8mm (7.77" x 2.87")
Color	Warm Gray
Material	Plastic Aluminum
Warranty	1 Year(s)


## ► Related Products

### Dome - Dome

B53		<p>3MP Indoor Dome with D/N, Adaptive IR, Superior WDR, Fixed lens, f1.9mm/F2.8 (HOV:129.56° (overview area), 79° (high detail area)), H.264, 1080p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IK09, DI/DO</p>
-----	---	--

E63A		5MP Indoor Dome with D/N, Adaptive IR, Basic WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:66.62°-28.88°), H.264, 1080p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE, IK09, DI/DO
E67		2MP Indoor Dome with Basic WDR, SLLS, Vari-focal lens
D71A		1MP Outdoor Dome with D/N, Adaptive IR, Fixed lens, f2.93mm/F2.0 (HOV:72°), H.264, 720p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP67, IK10, DI/DO
D82		3MP Outdoor Dome with D/N, Adaptive IR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:70.5°-28.2°), H.264, 1080p/30fps, DNR, MicroSDHC/MicroSDXC, PoE, IP67, IK10
E73A		5MP Outdoor Dome with D/N, Adaptive IR, Basic WDR, Fixed lens, f2.93mm/F2.0 (HOV:82.3°), H.264, 1080p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP67, IK10, DI/DO
E77		10MP Outdoor Dome with D/N, Adaptive IR, Basic WDR, Fixed lens, f3.6mm/F1.8 (HOV:101.4°), H.264, 1080p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP67, IK10, DI/DO
E83		5MP Outdoor Dome with D/N, Adaptive IR, Basic WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:69.2°-28.2°), H.264, 1080p/30fps, DNR, MicroSDHC/MicroSDXC, PoE, IP67, IK10
E83A		5MP Outdoor Dome with D/N, Adaptive IR, Basic WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:69.2°-28.2°), H.264, 1080p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP67, IK10, DI/DO
E84		2MP Outdoor Dome with D/N, Adaptive IR, Basic WDR, SLLS, Vari-focal lens, f2.8-12mm/F1.4 (HOV:92.5°-35.9°), H.264, 1080p/30fps, DNR, MicroSDHC/MicroSDXC, PoE, IP67, IK10
E85		1MP Outdoor Dome with D/N, Adaptive IR, Superior WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:60.1°-24.3°), H.264, 720p/30fps, DNR, MicroSDHC/MicroSDXC, PoE, IP67, IK10
E86		3MP Outdoor Dome with D/N, Adaptive IR, Superior WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:70.5°-28.8°), H.264, 1080p/30fps, DNR, MicroSDHC/MicroSDXC, PoE, IP67, IK10
KCM-7111		4MP Outdoor Dome with D/N, Basic WDR, Fixed lens, f2.8mm/F2.0 (HOV:82.6°), H.264, 1080p/15fps, DNR, Audio, MicroSDHC, PoE/DC12V, IP67, Vandal Proof, DI/DO

**Dome - Zoom Dome**

KCM-7311		4MP Outdoor Dome with D/N, Advanced WDR, SLLS, 3.6x Zoom lens, f3.3-12mm/F1.4-2.9 (HOV:77.2°-22.6°), P-Iris, Auto Focus, H.264, 1080p/15fps, 2D+3D DNR, Audio, MicroSDHC, PoE/DC12V, IP67, Vandal Proof, DI/DO
----------	---	--