

6030

Multi-Purpose Timer

Description

Altronix 6030 programmable timer is suitable for most functions that require a timed operation e.g. Applications, Siren/Bell Cut Off Module, Dialer Delay, Guard Tour Supervisory Timer, Pulsar / Flasher, etc.



6030

Specifications

Input

Voltage	6VDC or 12VDC selectable.
Current Draw	Stand-by: 3mA. Relay Energized: 75mA.

Relay

Contact Rating	8A/120VAC or 28VDC contacts. Relay activates at the end of the timing cycle.
----------------	---

Timer

Quick and extremely accurate time range adjustment from 1 second to 60 minutes.
Repeat (flasher/pulse) mode.

Indicators (LED)

Red	Indicates relay is energized.
-----	-------------------------------

Physical and Environmental

Dimensions (L x W x H)

3" x 2.5" x 0.75" (76.2mm x 63.5mm x 19.05mm).

Product Weight 0.1 lbs. (0.05 kg).

Shipping Weight 0.15 lbs. (0.07 kg).

Temperature

Operating -25°C to 55°C (-13°F to 131°F).

Storage -25°C to 70°C (-13°F to 158°F).

Relative Humidity 85% +/-5%.

Board Dimensions (L x W x H) and Drawing

3" x 2.5" x 0.75" (76.2mm x 63.5mm x 19.05mm)

