

# PD4UL

## UL Listed Power Distribution Module

### Description

Altronix PD4UL UL Listed Sub-Assembly power distribution module is designed to convert a single AC or DC input into four (4) individually fuse protected outputs.



PD4UL

### Specifications

#### Input

Voltage Range 12VDC or 24VDC, up to 10A or 24VAC or 28VAC, up to 12A.

#### Outputs

Four (4) fuse protected outputs.  
 2.5A per output max.  
 Total output current should not exceed max current rating of power supply employed.  
 Fuses are rated @ 3.5A/250V.

#### Indicators (LED)

DC Output Power LED.

#### Agency Listings

**UL:**  
 UL294 Access Control  
 UL603 Burglar Alarm  
 UL1481 Fire Alarm

**cUL:**  
 General Signaling Equipment Evaluated to CSA Standard C22.2 No.205-M1983.  
 Power Supplies for Burglar Alarm Systems ULC-5318-96.

#### Physical and Environmental

**Dimensions (L x W x H)**  
 5.25" x 3.25" x 1" (133.4mm x 82.6mm x 25.4mm).

**Product Weight** 0.15 lbs. (0.07 kg).

**Shipping Weight** 0.25 lbs. (0.11 kg).

**Temperature**  
 Operating 0°C to 49°C (32°F to 120°F).  
 Storage -20°C to 70°C (-4°F to 158°F).

**Relative Humidity** 85% +/-5%.

Mounting hardware included.

## PD4UL UL Listed Power Distribution Module

### Board Dimensions (L x W x H) and Drawing

5.25" x 3.25" x 1" (133.4mm x 82.6mm x 25.4mm)

