

# VertiLine48M

## Rack Mount DC Power Supply

### Description

Altronix Vertiline48M Rack Mount DC Power Supply provides sixteen (16) filtered and electronically regulated 56VDC power outputs in a space saving 2U EIA 19" rack mount chassis.



VertiLine48M

### Specifications

#### Input

Voltage 115VAC, 50/60Hz, 5A.

#### Output

Voltage 56VDC.  
 Current 6.5A max. total supply current.  
 Fusing Individual outputs' fuses rated @ 3.5A.  
 Other Short circuit and thermal overload protection.  
 Filtered and regulated.

#### Indicators (LED)

Master Illuminated master power disconnect circuit breaker with manual reset.  
 Output Sixteen (16) individual LEDs.

#### Physical and Environmental

Dimensions (H x W x D)  
 3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm).  
 Product Weight 13.75 lbs. (6.24 kg).  
 Shipping Weight 14.75 lbs. (6.69 kg).  
 Temperature  
 Operating 0°C to 49°C (32°F to 120°F).  
 Storage -20°C to 70°C (-4°F to 158°F).  
 Relative Humidity 85% +/-5%.  
 BTU/Hr. (approx.): 186 BTU/Hr.