
## BC Beam Clamp – BC





• Easy installation to beam flanges





| Part Number                 | BC                 |
|-----------------------------|--------------------|
| Material                    | Spring Steel       |
| Finish                      | nVent CADDY Armour |
| Rod Size 1 (RS1)            | 1/4"               |
| Rod Size 2 (RS2)            | #10                |
| Hole Size (HS)              | 7/16"              |
| Flange Thickness (FT)       | 1/2" Max           |
| Torque (TQ)                 | 20 in lb           |
| Static Load (F)             | 100 lb             |
| Certifications              | cULus              |
| Standard Packaging Quantity | 100 рс             |
| UPC                         | 78285619100        |

Setscrew must be tightened and torqued onto the sloped side of the I-beam.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved nVent, nVent CADDY, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

