



IR & Speciality


Height Strip Camera

HSW-H37


Features:

- 700 TVL color camera with 3.7mm wide angle lens
- Redesigned for easy installation
- Fits most standard door frames
- Durable aluminum construction
- Highly visible color coded height levels
- Curved surface with 180° HFOV camera adjustment
- Wrap-around labels visible from side
- 12VDC and 24VAC models
- 1 onboard camera included with base model
- Also available in black and silver

Height strip cameras are designed to supplement standard surveillance cameras by capturing a person's facial image and height upon exiting a store. The HSW-H37 includes a 700 TVL camera with OSD menu control. It is housed in a low profile enclosure with discrete 1/8" viewing slots. The camera can be adjusted to cover a full 90 degrees to the left and right of center, making it ideal for double doors requiring an angled view. Up to 2 additional cameras can be installed for multiple viewing angles.



The HSW-H37 is sized to fit most standard door frames (1.7" width) and has cable entry through the top, bottom and rear of the unit allowing it to be installed in a wide variety of environments. Two additional cameras can be added and the unit can be mounted between two doors to cover both entrance and exit with a single unit.





HSW-H37

700 TVL Height Strip Camera

■ Inside view



■ Specifications

Model	HSW-H37
Image Sensor	1/3" Sony EXview HAD CCD II
Effective Pixels	976 (H) x 494 (V)
Scanning Frequency	59.94Hz (V)
Scanning System	2:1 Interlace
Sync. Type	Internal
Resolution	700 TVL
S/N Ratio	More than 50dB (AGC OFF)
Day/Night Performance	Digital Day/Night
Video Output	1.0 Vp-p composite 75Ω
Min. Illumination	0.1 lux @ 30 IRE (F2.0)
Gamma Correction	0.45
OSD Languages	English, Japanese, German, French, Russian, Portuguese, Spanish
White Balance	ATW, Push, User 1, User 2, Anti CR, Manual, Push Lock
Shutter Speed	1/60 ~ 1/100,000 sec
Backlight	BLC / HLC / Off
AGC	On / Off
Motion Detection	On / Off (4 areas)
Privacy Zone	On / Off (4 areas)
Noise Reduction (NR)	On / Off (level adjustable)
Adaptive Tone Reproduction (ATR)	On / Off (level adjustable)
Picture Adjustment	Mirror, Brightness, Contrast, Sharpness, Hue, Gain
Lens	3.7mm (74° HFOV)
Camera ID	0~9, A~Z, Special Character
Power Supply	12VDC (24VAC optional)
Power Consumption	Max. 80mA
Operating Temperature	14° ~ 122° F (-10° ~ 50° C)
Ambient Humidity	90% RH
Dimensions	1.7" W x 1.4" D x 34.1" H
Weight	2 lbs. / 907g
Optional Accessories	CAM-HS37 - Color camera with 3.7mm lens (Two additional cameras can be added to unit)
Color & Power Options	HSW-H37 - white, HSS-H37 - silver, HSB-H37- black / Add "-24" for 24VAC power

All specifications are subject to change without notice

