

### CM-40/41

### 4 1/2" ROUND ALL-ACTIVE SWITCHES



CM-40/2



CM-41/3



CM-40/4

#### FEATURES

- LARGE, EASY TO OPERATE SWITCHES
- 4 1/2" ROUND FACEPLATES
- ALL-ACTIVE DESIGN REQUIRES MINIMAL ACTUATION FORCE
- MEETS ADA REQUIREMENTS
- DURABLE STAINLESS STEEL OR SOLID BRASS CONSTRUCTION
- FLUSH MOUNT OR SURFACE MOUNT
- UL/CSA APPROVED SWITCH, RATED 15 AMPS @30V DC
- VARIOUS LOGOS & MESSAGES
- ARCHITECTURAL FINISHES

#### DESCRIPTION

**CAMDEN DOOR CONTROLS CM-40/41 Series** all-active switches are heavy-duty, ADA-compliant door controls. The 4 1/2" round faceplates are stainless steel or solid brass, and the assembly is designed for easy installation.

The CM-40 and CM-41 switches mount to standard 2 x 4 electrical boxes. The SPDT (and optional DPDT) switches are UL/CSA approved, and rated 15 amps @ 30 VDC.

The 4 1/2" square stainless steel backplate on the CM-41 is large enough to dress-up (cover) a poorly installed electrical box. It will also fit perfectly on most 4 1/2" surface boxes.

#### APPLICATION

Camden all-active switches are designed for areas where an easy-to-activate, high visibility switch is desired. Ideal for high-traffic areas, hospitals, wheelchair access, seniors' residences, etc. They can be surface or flush mounted.

Camden all-active switches are designed to control electric strikes, electromagnetic locks and automatic doors. They may also be used for shunting, bypassing alarms, request to exit, timed functions, and many other applications.

The switches are made for high frequency usage, in both indoor and outdoor environments. Camden switches are versatile, and can be supplied in various configurations and finishes, to suit any commercial, industrial, or residential application.

#### ARCHITECTS/ENGINEERS SPECIFICATIONS

The switches to be used throughout the complex shall be Camden Door Controls CM-40 or CM-41 series all-active switches.

The switches shall be easy-to-activate, ADA compliant, 4 1/2" round in diameter. Switches shall be all-active, whereby pressing any part of the faceplate will activate the device. Faceplates shall be constructed of 18-gauge stainless steel or solid brass, and have concealed mounting screws for tamper resistance. Switches shall use plastic spacers and rubber dampers for noise reduction. Switches shall be rated at a minimum of 15 amps @ 30V DC.

## 4 1/2" ROUND ALL-ACTIVE SWITCHES

### ORDERING INFORMATION

All CM-40/41 series all-active switches are complete ready-to-install assemblies. They are supplied with stainless steel Allen screws and an Allen wrench for mounting.

MODEL	DESCRIPTION
<b>4 1/2" ROUND (114MM)</b>	
CM-40/1	ROUND STAINLESS STEEL PLATE, NO EMBOSING
CM-40/2	EMBOSSED WITH WHEELCHAIR LOGO IN BLUE
CM-40/3	EMBOSSED WITH PUSH TO OPEN LOGO IN BLACK
CM-40/4	EMBOSSED WITH WHEELCHAIR LOGO AND PUSH TO OPEN LOGOS IN BLUE
CM-40/5	WHEELCHAIR LOGO, PUSSEZ POUR OUVRIER
CM-40/C	CUSTOM ENGRAVING, PLEASE SPECIFY WHEN ORDERING
<b>4 1/2" ROUND FRONT, SQUARE BACKPLATE</b>	
CM-41/1	ROUND STAINLESS STEEL FACEPLATE/ SQUARE BACKPLATE, NO EMBOSING
CM-41/2	EMBOSSED WITH WHEELCHAIR LOGO IN BLUE
CM-41/3	EMBOSSED WITH PUSH TO OPEN LOGO IN BLACK
CM-41/4	EMBOSSED WITH WHEELCHAIR LOGO AND PUSH TO OPEN LOGOS IN BLUE
CM-41/5	WHEELCHAIR LOGO, PUSSEZ POUR OUVRIER
CM-41/C	CUSTOM ENGRAVING, PLEASE SPECIFY WHEN ORDERING

### OPTIONS/FINISHES:

- DP Add DP to product # to order DPDT switch instead of SPDT switch
- WR Add WR to product # for weather resistant boot
- WT Add WT to product # for boot and water tight coating
- AL Add AL to product # for arrow left
- AR Add AR to product # for arrow right
- AB Add AB to product # for antique brass finish (US5/C5)
- PB Add PB to product # for polished brass finish (US3/C3)
- SB Add SB to product # for satin brass finish (US4/C4)
- OB Add OB to product # for oil rub bronze finish (US10B/C10B)
- MS Add MS to product # for mirrored stainless steel finish (US32/C32)

