




4680C

2 WIRES AUDIO/VIDEO UNIT



Simplebus 2 system audio/video unit with terminal block complete with front-adjustable wide-angle 1.3" CCD colour camera and LED camera illumination. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electrets microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. Audiovisual indications for disabled individuals assistance request can be activated via programming. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay. For use in modules Art. 33410, 33411 and 33412. Dimensions: 102x55x38 mm. Compatible with all Simplebus 2 functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.



4680C

2 WIRES AUDIO/VIDEO UNIT

GENERAL DATA

Type	Audio and video unit
Height (inch) (pc)	24.09
Width (inch) (pc)	12.99
Depth (inch) (pc)	10.16
Product color	White
Product weight (oz) (oz)	7.05
Type of finishing materials	ABS

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888CU	Yes
---	-----

AUDIO FEATURES

Microphone	9.7 (∅), omnidirectional
Loudspeaker	50mm (∅), 8 Ohm, 0.2W
Technologies implemented	Echo canceling

CAMERA FEATURES

Camera	Colors
Sensor type	1/3" CMOS
Camera orientation	Vertical

ELECTRICAL CHARACTERISTICS

Type of power supply	External power supply
Supply voltage	33VDC

HARDWARE FEATURES

Clamps	L L V+V- RTE DO PR GND SE COM NC NO
Removable terminals	Yes
Number of inputs (n°)	2



4680C

2 WIRES AUDIO/VIDEO UNIT

HARDWARE FEATURES

Number of outputs (n°)	2
------------------------	---

SETTINGS

Loudspeaker volume	Yes
--------------------	-----

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°F) (°F)	-13 ÷ 131
---------------------------------	-----------

Operating humidity (RH max) (%)	25 ÷ 95
---------------------------------	---------

Environmental class	III
---------------------	-----

CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
-------------------	--

MAIN FUNCTIONS

Door opener	Yes
-------------	-----

Number of auxiliary relays (n°)	1
---------------------------------	---

Input for local door release button	Yes
-------------------------------------	-----

Door open signaling input	Yes
---------------------------	-----

Visual indications of system status	Yes
-------------------------------------	-----

Acoustic signals of system status	Yes
-----------------------------------	-----

Speech synthesis of system status	Yes
-----------------------------------	-----

GENERAL FEATURES

Door release (dry contact bridge)	Yes
-----------------------------------	-----

Minimum illumination (lux)	0.35
----------------------------	------

Acoustic signalling	Yes
---------------------	-----

Visual signalling	Yes
-------------------	-----

Speech synthesis	Yes
------------------	-----

Simplebus 2 audio/video system	Yes
--------------------------------	-----

Door release (direct current output)	Yes
--------------------------------------	-----

Video output	1Vpp 75PAL
--------------	------------