



8561IV

IKALL KIT AND MINI HF WI-FI VIP



Ikall kit and Mini HF Wi-Fi. ViP system



8561IV

IKALL KIT AND MINI HF WI-FI VIP

KIT PRODUCTS



6742WK White HF Mini Monitor WI-FI/GW for ViP KIT

Hands-free Wi-Fi colour monitor for ViP system pre-programmed for kit art. 8561IV. 4.3" / 16:9 colour screen. Resolution 480x272 pixels. Allows backlighting intensity, audio volume and ringtone volume adjustment. Equipped as standard with 7 soft touch buttons: key button with door open indicator LED, privacy function button with indicator LED, 4 programmable buttons and 1 menu access button. Features 3 inputs that can be programmed for various functions. Can also be used in standard POE systems. The ringtone and the video memory function with absent message can be customised. H.264 video format. Dimensions (L x H x P): 115x160x22 mm.

GENERAL DATA

Height (inch) (pc)	37.8
Width (inch) (pc)	27.17
Depth (inch) (pc)	5.2
Product color	White RAL9003
Product weight (oz) (oz)	15.17
Type of finishing materials	ABS
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

ViP	Yes
-----	-----

DISPLAY FEATURES

Display size (")	4.3
Aspect Ratio	16:9
Resolution (pixels)	480x272
OSD menu	Yes

AUDIO FEATURES



8561IV

IKALL KIT AND MINI HF WI-FI VIP

Induction loop function	Yes
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	36mm (Ø), 8 Ohm, 1W

ELECTRICAL CHARACTERISTICS

Type of power supply	PoE
PoE power supply	Standard IEEE 802.3af, Comelit PoE (56VDC)
Absorption in stand-by (W)	2.64
Maximum absorption (W)	3.52

HARDWARE FEATURES

Type of buttons	Capacitive
Service buttons	Answer, Silent (Privacy), Menu, Messages, Door open
No. of programmable buttons for additional functions	4
Clamps	- IN1 IN2 IN3
Number of inputs (n°)	3
Communication ports	RJ45 (Ethernet)

SETTINGS

Loudspeaker volume	Yes
Ringtone volume	Yes
Screen backlight	Yes

NETWORK AND COMMUNICATION PROTOCOLS

Type of LAN network	Ethernet 10/100 Mbit/s, IEEE 802.3, IEEE 802.3u (Fast Ethernet)
Type of Wi-Fi connection	IEEE 802.11 b/g/n, 2.4 Ghz, 13 channels
Encryption and authentication method supported	OPEN WPA-PSK networks, TKIP WPA2-PSK, AES WEP 64 bits (5-digit ASCII or 10 hexadecimal codes), WEP 128 bits (13-digit ASCII or 26 hexadecimal codes), WPS authentication (supported for WPA2-PSK)
IP address assignment	DHCP



8561IV

IKALL KIT AND MINI HF WI-FI VIP

NETWORK AND COMMUNICATION PROTOCOLS

IoT connection to Comelit Cloud	Yes
Firmware update via Comelit Cloud	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

Protection rating (IP code)	IP30
Operating temperature (°F) (°C)	41 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), RED 2014/53/UE (EN 60950-1:2006+A11:2009+A1:2010+A12:2011, +A2:2013, EN 62311:2008, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)

MAIN FUNCTIONS

Compatibility with Video Entry Comelit App	Yes
Door opener	Yes
Self Activation	Yes
Intercom calls	Yes
Actuator control	Yes
CPS call	Yes
Outside door call input	Yes
Silent mode (Privacy)	Yes
Video memory	Yes
Door opening on call (Doctor)	Yes
Automatic answer (handsfree)	Yes
Door open signaling	Yes
Call forwarding	Yes
Customisable ringtone	Yes
Sending alarm calls	Yes



8561IV

IKALL KIT AND MINI HF WI-FI VIP

MAIN FUNCTIONS

Date/time display	Yes
Sending e-mail on event	Yes
Receiving ViP messages	Yes
ViP anti-theft function	Yes



8561IV

IKALL KIT AND MINI HF WI-FI VIP



4894HIM External unit for ViP kit - Ikall Metal H264

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKD. The external unit is coded with ViP address 100 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H264 video format

GENERAL DATA

Flush-mounted	Yes
---------------	-----

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°F) (°F)	-13 ÷ 131
---------------------------------	-----------



8561IV

IKALL KIT AND MINI HF WI-FI VIP



1441B 30W VIP SYSTEM POWER SUPPLY UNIT

Power supply unit with 110Vac/240Vac input and 48Vdc output. 30W power. DIN bar power supply unit (4 DIN modules). Dimensions: 72x93x56mm

MAIN FEATURES

Supply voltage	110÷240
Number of DIN modules (n°)	4

GENERAL DATA

Height (inch) (pc)	14.65
Width (inch) (pc)	21.26
Depth (inch) (pc)	16.54
Operating temperature (°F) (°F)	14 ÷ 122

ELECTRICAL SPECIFICATIONS

Maximum current absorption (mA)	900
Maximum power delivered (W)	30



8561IV

IKALL KIT AND MINI HF WI-FI VIP



1595 120-230VAC / 33VDC POWER SUPPLY UNIT

Power supply unit with input of 120÷230VAC, 33VDC output with 500mA continuous and 1.2A inrush current for video door entry panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).

MAIN FEATURES

Supply voltage	120÷230 VAC
Output supply voltage	33VDC
Max. current delivered (A)	0.5
Maximum inrush current (A)	1.2
Applicable to DIN rail	Yes
Number of DIN modules (n°)	4

GENERAL DATA

Height (inch) (pc)	14.65
Width (inch) (pc)	16.94
Depth (inch) (pc)	21.26
Type of finishing materials	Plastic
Product color	White
Operating temperature (°F) (°F)	-4 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 90

COMPATIBILITY

Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes



8561IV

IKALL KIT AND MINI HF WI-FI VIP

ELECTRICAL SPECIFICATIONS

Maximum power delivered (W)	60
-----------------------------	----



8561IV

IKALL KIT AND MINI HF WI-FI VIP



1440 IP (VIP) FLOOR SWITCH

PoE Ethernet switch with 2 ports (10/100 Mb) and 4 ports (10 MB).
Dimensions 66 x 85 x 35 mm

MAIN FEATURES

Height (inch) (pc)	21.02
Width (inch) (pc)	17.01
Depth (inch) (pc)	14.65
Operating temperature (°F) (°F)	41 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 75
DIN rail mounted	Yes
DIN modules (no.) (n°)	4

COMPATIBILITY

Vip system	Yes
------------	-----

CONNECTIVITY

Type of connections/ports	RJ45
---------------------------	------