



HFX-7000MW

Quadra Kit and Mini HF Wi-Fi. S2



The kit consists of no. 1 external unit Quadra art. EX-DSM, no. 1 power supply art. 1209/4, and no. 1 monitor Mini hands-free Wi-Fi art. EX-7000HW The kit is pre-programmed and ready to use.

AWARDS

DESIGN
MILANO

DESIGN PLUS
awarded by building



HFX-7000MW

Quadra Kit and Mini HF Wi-Fi. S2

KIT PRODUCTS



EX-7000HW

Mini Handsfree Wi-Fi monitor. S2

Wall-mounted hands-free monitor with full-duplex audio and 4.3" / 16:9 colour screen. It is equipped with a Wi-Fi port to allows calls forwarding to mobile devices. Allows brightness control, plus adjustment of the ringtone volume, which can be customised by choosing one of several different melodies. Equipped as standard with 8 sensitive touch back-lit controls for audio activation, door-opening, self-ignition, switchboard call, privacy service and LED signalling for the door status. Manages floor door calls as standard. Complete with 2 x 8-position dip-switch for user code programming and button programming. The wall-mounting backplate is included. Dimensions: 4.53"x6.3"x0.87".

GENERAL DATA

Height (inch) (pc)	37.8
Width (inch) (pc)	27.17
Depth (inch) (pc)	5.2
Product color	White
Type of finishing materials	Plastic
Wall-mounted	Yes
Desk base-mounted	Yes
Audio/video system	Yes

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888CU	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes

DISPLAY FEATURES

Touch screen	Yes
Resolution (pixels)	480x272
OSD menu	Yes



HFX-7000MW

Quadra Kit and Mini HF Wi-Fi. S2

DISPLAY FEATURES

Type of display	LCD
-----------------	-----

ELECTRICAL CHARACTERISTICS

Supply voltage	22 ÷ 28VDC
----------------	------------

HARDWARE FEATURES

Clamps	L L CFP1 CFP2
Removable terminals	Yes
Total buttons (n°)	8
LED signaling (no.) (n°)	4

SETTINGS

Loudspeaker volume	Yes
Screen brightness	Yes

NETWORK AND COMMUNICATION PROTOCOLS

Type of Wi-Fi connection	IEEE 802.11 b/g/n, 2.4 Ghz, 13 channels
--------------------------	---

ENVIRONMENTAL AND COMPLIANCE FEATURES

Protection rating (IP code)	IP30
Operating temperature (°F) (°F)	5 ÷ 39.2
Operating humidity (RH max) (%)	25 ÷ 75

MAIN FUNCTIONS

Comaptibility with Video Entry Comelit App	Yes
Door opener	Yes
Self Activation	Yes
Intercom calls	Yes
Actuator control	Yes
CPS call	Yes



HFX-7000MW

Quadra Kit and Mini HF Wi-Fi. S2

MAIN FUNCTIONS

Outside door call input	Yes
Silent mode (Privacy)	Yes
Door opening on call (Doctor)	Yes
Call forwarding	Yes
Multiple address	Yes
Customisable ringtone	Yes
Priority calls	Yes
Selective intercom call	Yes

FEATURES

Absorption during call (mA)	180
Absorption during communication (mA)	300



HFX-7000MW

Quadra Kit and Mini HF Wi-Fi. S2



**EX-
DSM**

2-WIRE VIDEO KIT QUADRA EXTERNAL UNIT

Quadra series wall-mounted external video entry unit with mechanical buttons. Die-cast aluminium faceplate, wide-angle colour camera and a single LED for nighttime lighting. Indicator LED for call sent, lock-release activated, audio activated and system busy. Adjustment of speaker volume and audio balance. Power supply from bus line. External unit dimensions: 3.74"x7.68"x1.1".

GENERAL DATA

Wall-mounted

Yes

HARDWARE FEATURES

Clamps

LL RTE COM DO SE- SE+C NC NO

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°F) (°F)

-13 ÷ 131



HFX-7000MW

Quadra Kit and Mini HF Wi-Fi. S2



1209/4 4 OUTPUT POWER SUPPLY FOR 2-WIRE VIDEO KIT

Power supply for 2-wires video kit, 4 monitor outputs.



HFX-7000MW

Quadra Kit and Mini HF Wi-Fi. S2

ACCESSORIES



4793MC CORTEN FACEPLATE FOR QUADRA W/BUTTONS

Corten color faceplate for Quadra entrance panel with mechanical buttons.



4793MB BLACK FACEPLATE FOR QUADRA W/BUTTONS

Black faceplate for Quadra entrance panel with mechanical buttons.



4793MA ALUMINIUM FACEPLATE FOR QUADRA W/BUTTONS

Aluminium colour faceplate for Quadra entrance panel with mechanical buttons



4791 Adapter plate for Quadra

Plate allowing installation of the Quadra external unit in 1- and 2-module flush-mounted boxes by Comelit, Bticino and Urmet. Dimensions 137x236 mm



4792 RAIN SHIELD FOR QUADRA ENTRANCE PANEL

Rain shield in painted aluminum for Quadra entrance panel, grey colour. Dimensions (W x H x D): 99 x 210 x 41 mm.



EX-9000H 7" MAXI MONITOR. S2 SYSTEM FOR USA



HFX-7000MW

Quadra Kit and Mini HF Wi-Fi. S2

ACCESSORIES



EX-8000H


ICON SERIES HANDS-FREE COLOUR MONITOR. S2

Door-entry phone with electronic call function, conversation button on base, call volume control and privacy function, door open button and supplementary button or additional services with independent common. On this model it is not possible to add extra buttons or LEDs. Dimensions: 95x215x58 mm.



EX-7000H

COLOUR HANDS-FREE MINI MONITOR, S2



1217

NAME TAG SHEETS FOR QUADRA ENTRANCE PANEL

The kit contains 10 sheets of adhesive labels for nameplates



1209/8

8 OUTPUT POWER SUPPLY FOR 2-WIRE VIDEO KIT

Power supply for 2-wires video kit, 8 outputs for the monitors.



6732

DESK BASE FOR HANDSFREE MINI MONITOR

Desk base for desktop conversion of Handsfree Mini monitor. Complete with 1x 2 metre cable with RJ45 connector to connect monitor terminals to the coupler or domestic series socket. Dimensions: 140x190x140mm.



HFX-7000MW

Quadra Kit and Mini HF Wi-Fi. S2

ACCESSORIES



1235A NAMEPLATE LABEL PRINTING SOFTWARE

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website



1409 ACCESSORY FOR REMOTE COLOUR CAMERAS, 2-WIRE SYSTEM

Remote camera module for Simplebus 2 2-wire digital systems. Allows management of up to 3 colour cameras in cyclical sequence from door entry monitors using a dedicated button. 12 Vac or 20 Vdc power supply. Dimensions: 60x85x35 mm (4 DIN modules).



1256 ACTUATOR RELAY

Intelligent Simplebus device for controlling a relay on board (12÷24 VAC/VDC - 10A max). For use and programming of the function required, follow the indications given in the technical documentation. It can be used in Simplebus system. Power supply: 12 VAC or 20 VDC. Dimensions: 66X85X35mm (4 DIN modules). Line branch terminal art. 1214/2C in equipment.