



DTK-3VWMUSB 3-Outlet Surge Protector

DITEK's DTK-3VWMUSB 3 Outlet Charging Stations are the next wave in power distribution devices that combine DITEK's trusted surge protection with a modern look and feel. Your sensitive electronics are safe with features like an illuminated load-status indicator, 3 AC Outlets and 2 USB charging ports.

Is your circuit overloaded? Now you know the answer. Green = Safe; Orange = Warning; Red = Maximum, Flashing Red = Overload.



Product Features

- 120VAC – 15A
- Illuminated load-status indicator with different colors for each level of load status
- 2 port USB charger (total 5V / 2.4A)

Applications

- Cell Phones, Tablets, Other USB Devices
- Counter Appliances, Home Office, Bedroom

LED Colors for Different Levels of Load Status:



Technical Specifications

Voltage Configuration:	120VAC Single Φ
MCOV:	127VAC
Protection Modes:	L-N, L-G, N-G
Voltage Protection Rating:	500V
Surge Current Rating:	36,000A
Max. Continuous Current:	15A
Nominal Discharge Current Rating (I_n):	3kA
Operating Frequency:	50/60Hz

Mechanical Specifications

Connection Method:	NEMA 5-15P
Housing:	ABS
Dimensions:	5.25" L X 3.75" W x 1.13" H (133.35 mm x 95.25 mm x 28.58 mm)
Weight:	0.5 lb (0.23 kg)

Quality Standards & Approvals

Certifications:	UL1449 4 th Edition
SPD Type:	Type 3
Warranty:	10 Year Limited Warranty

