

# DTK-SL “Snap-Lite” Series

66 Block Quick-Connect Surge Protectors



## Product Features

- Quick connect module – no bridge clips required!
- Each Snap-Lite protects one pair
- Field-replaceable modules
- Self-resetting fuse on models with “A” suffix
- Models available for both current-limited and standard lines

## Applications

- Voice/Data Professionals

## Note

- Each 66 Block requires one ground bar: DTK-SIGB



**DITEK’s DTK-SL Series** quick-connect line protectors are designed specifically for Voice/Data professionals. The Snap-Lite provides both voltage and current limiting in addition to surge protection. The unique multi-function diagnostic LED shows protection status, line continuity and line usage. Available in four different voltages, there is a Snap-Lite for virtually any analog 66 block application.

## Technical Specifications

DTK-	SL30	SL50	SL95	SL130
<b>Service Voltage:</b>	30V	50V	95V	130V
<b>MCOV:</b>	38VDC	66VDC	127VDC	175VDC
<b>Clamping Voltage:</b>	47V	82V	150V	204V
<b>Protection Modes:</b>	Tip-Ground, Ring-Ground			
<b>Surge Current Rating:</b>	1,000 Amps per pair	5,000 Amps per pair	4,000 Amps per pair	4,000 Amps per pair
<b>Max Continuous Current:</b>	“-A” models 150mA “-B” models 2A			

## Mechanical Characteristics

<b>Base Connection Method:</b>	Press-to-Fit connection to 66 Block
<b>Housing:</b>	High Impact Plastic
<b>Operating Temperature:</b>	-40°F - 158°F (-40°C - 70°C)
<b>Maximum Humidity:</b>	95% non-condensing
<b>Dimensions:</b>	.324”L x .38”W x 1.56”H (82.3mm x 9.6mm x 39.6mm)
<b>Weight:</b>	.5oz (14g)

## Quality, Standards & Approval

<b>Agency Approvals:</b>	“-A” models UL497A “-B” models UL497B
<b>Warranty:</b>	Ten Year Limited Warranty

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.

