

D308 Field test kit for D296/D297

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Four calibrated neutral density filters
- ▶ Clip to hold filter and mount on pole

The D308 Field test kit provides a calibrated amount of obscuration between the transmitter and receiver of the D296 and D297 Beam smoke detectors. This allows testing of the transmitter/receiver alignment and measuring the beam intensity.

Certifications and approvals

Region	Regulatory compliance/quality marks	
USA	UL	ANSI/UL 268, Smoke Detectors for Fire Alarm Systems
	CSFM	see www.boschsecurity.com (the Bosch website)
Canada	ULC	CAN/ULC-S529, Smoke Detectors for Fire Alarm Systems

Parts included

Quantity	Component
1	Handle with spring clip
4	Test screens (20%, 40%, 60%, and 80%)

Technical specifications

Mechanical

Dimensions (LxWxH)	9.02 in. x 9.49 in. x 2.52 in. (22.9 cm x 24.1 cm x 6.4 cm)
Weight	
Gross	1.08 lb. (0.49 kg)
Net	14.36 oz. (0.407 kg)

Ordering information

D308 Field test kit for D296/D297

Allows testing the calibration of the D296 and D297 beam smoke detectors
Order number **D308**