

## **TIC651**

## 6.5" 25/70/100V IN CEILING 2-WAY POWERED BY SONIC VORTEX®

Performs great as a combo audio speaker and paging speaker. Our Sonic Vortex<sup>®</sup> technology generates rich, deep bass and effortless clarity from what most people would call a 'back box', but is not. It is actually a compact, integrated tuned enclosure. This patented technology is a 'twist' on Ported Transmission Line design, that optimizes air movement to produce astonishing sound. The enclosure also keeps sound from bleeding to other rooms while adding 6 to 9dB boost in mid-lower bass. Designed to play in full range mode only.



Optional EZBracket pre-construction bracket; use size "F" for this model.

- Woofer: 6.5" Ribbed Injected Polypropylene
- Frequency/Crossover Setting: Full Range Mode Only
- Tweeter: 1" Aluminum Dome
- Surround: Butyl Rubber
- Coaxial Tweeter Design
- 25V Taps: 2.5, 1.3, 0.7, 0.4, 0.2 Watts
- 70V Taps: 20, 10, 5, 2.5, 1.3 Watts
- 100V Taps: 20, 10, 5, 2.5 Watts
- Low Impedance Bypass: 8Ω
- Power Handling (8Ω): 5-120W
- Speaker Weight: 7.1lbs (3.2 kg)
- Cutout: 8.4" (214 mm)
- Grille Diameter: 9.4" (239 mm)
- Depth: 6.8" (172 mm)
- Installed Frequency Response: 48 Hz 20 kHz
- Sensitivity: 91 db
- Grille: Magnetic Bezelless; White Paintable
- Connector Type: Push Terminals
- Pre-construction Bracket: EZBracket Size: F



TIC651 Tap

Multiple International Patents Awarded Additional Patents Pending

