

RECESSED DOOR/WINDOW CONTACT

2GIG-DW20R-345



The Recessed Door Contact (2GIG-DW20R-345) is the industry's most flexible supervised door contact. It communicates wirelessly with the control panel via the 345 MHz frequency. It also allows a multitude of applications while hiding the transmitter within a door or window frame. It is powered by a replaceable lithium battery and should last five (5) years under normal usage.

SPECIFICATIONS

Wireless Signal Range	450 ft (137.2 m), open air, with Wireless Control Panel
Code Outputs	Alarm; Alarm Restore; Supervisory; Low Battery
Transmitter Frequency	345.000 MHz (crystal controlled)
Unique ID Codes	Over one (1) million different code combinations
Supervisory Interval	70 minutes
Magnet Dimensions (H x D)	0.5 x 0.75 in (1.27 x 1.9 cm)
Magnet Type	Rare Earth
Sensor Dimensions (H x D)	2.57 x 0.75 in (6.53 x 1.9 cm)
Weight (including battery & magnet)	1.25 oz (35.4 g)
Housing Material	ABS Plastic
Color	White
Operating Temperature Limits	32°-120 F° (0°-49° C)
Relative Humidity	5-90% Non-Condensing
Battery (installed with pull tab)	One (1) 3V CR-2 or equivalent Lithium battery
Certification	Anatel, ETL, FCC, IC, and NOM

Nortek Security & Control | 1950 Camino Vida Roble Suite 150 | Carlsbad, CA 92008 | USA | 800.421.1587 | nortekcontrol.com | dealer.2gig.com

Copyright © 2015 Nortek Security & Control LLC. All Rights Reserved. Go!Control is a registered trademark of Nortek Security & Control LLC. All other products or name brands are either trademarks or registered trademarks of their respective holders. Specifications and product availability subject to change without notice. For more information, contact your local Nortek Security & Control or 2GIG dealer for pricing or visit linearcorp.com or dealer.2gig.com.