

IP Performance You Want at the Price You Need













Upgrading to IP has never been so easy and affordable.

Choose from our full range of quality IP cameras and our intuitive and cost-effective Embedded NVRs with a user-friendly configuration process that takes you to live video after only minutes of setup time. With built-in network switches that also supply power to the cameras, installing IP video has never been easier.










Performance Series IP Cameras

Honeywell's expanded range of ONVIF-compliant IP cameras gives you increased flexibility and the freedom to choose what's right for your installation.



	PART NUMBER	DESCRIPTION	ENVIRONMENT	IR ILLUMINATION*	LENS	RECOMMENDED ACCESSORIES
IR BALL	 HED2PER3	2MP DWDR TDN IR Ball camera PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 82ft (25 m)	2.8mm fixed, F2.0	Junction Box: HQA-BB1; Wall Mount: HQA-WK2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM; Pendant Mount: HQA-PK
	 HEW2PER3	2MP WDR True Day/Night IR Ball camera white, PoE 802.3af or 12 VDC		Smart IR, up to 164ft (50 m)	2.8mm fixed, F1.6	Junction Box: HQA-BB1, HQA-BB3; Wall Mount: HQA-WK2; Pole Mount: HQA-PM2; Corner Mount: HB34S2- CM; Pendant Mount: HQA-PK
	 HEW4PER3	4MP WDR True Day/Night IR Ball camera, PoE 802.3af or 12 VDC		Smart IR, up to 82ft (25 m)	2.8mm fixed, F2.0	Junction Box: HQA-BB1; Wall Mount: HQA-WK2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM; Pendant Mount: HQA-PK
	 HEW4PER3B	4MP WDR True Day/Night IR Ball camera grey, PoE 802.3af or 12 VDC		Smart IR, up to 164ft (50 m)	2.8mm fixed, F1.6	Junction Box: HQA-BB1, HQA-BB3G; Wall Mount: HQA-WK2G; Pole Mount: HQA-PM2B; Corner Mount: HB34S2- CMB; Pendant Mount: HQA-PK
	 HEW2PER2	2MP WDR True Day/Night IR Ball camera white, PoE 802.3af or 12 VDC		Smart IR, up to 164ft (50 m)	2.7-13.5mm MFZ, F1.4	Junction Box: HQA-BB2, HQA- BB2G, HBS2-BB, HEJB; Wall Mount: HQA-WK, HQA-WKB; Pole Mount: HQA-PM2, HQA-PM2B; Corner Mount: HB34S2-CM, HB34S2-CMB; Rainshield: HQA-RS
	 HEW4PER2	4MP WDR True Day/Night IR Ball camera white, PoE 802.3af or 12 VDC		Smart IR, up to 164ft (50 m)		
	 HEW4PER2B	4MP WDR True Day/Night IR Ball camera grey, PoE 802.3af or 12 VDC		Smart IR, up to 164ft (50 m)		
IR MICRO-DOME	 H2W2PER3	2 MP WDR True Day/Night IR Micro-Dome Camera with built-in microphone, PoE 802.3af or 12 VDC	IP66 rated IK10 vandal resistant	Smart IR, up to 66 ft (20 m)	2.8mm fixed, F2.0	Junction Box: HQA-BB3; Wall Mount: HQA-WK2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM; Pendant Mount: HQA-PK
	 H2W4PER3	4 MP WDR True Day/Night IR Micro-Dome Camera with built-in microphone, PoE 802.3af or 12 VDC		Smart IR, up to 66 ft (20 m)	2.8mm fixed, F2.0	
	 H2W2PC1M	2 MP WDR True Day/Night people counting Camera built-in microphone, PoE 802.3af or 12 VDC		N/A	2.1mm fixed, F2.0	
FISHEYE	 HFD5PR1	5 MP Day/Night DWDR Rugged Fisheye Camera with built-in microphone	IK10 vandal resistant	N/A	1.42mm fixed F2.6	Junction Box: HQA-BB2; Wall Mount: HQA-WK; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM; Pendant Mount: HQA-PK
PIN HOLE	 HPW2P1	2 MP WDR IP Pin-Hole Camera, 12 VDC	N/A	N/A	2.8 mm fixed F2.4	




* Depending on scene reflectance.






		PART NUMBER	DESCRIPTION	ENVIRONMENT	IR ILLUMINATION*	LENS	RECOMMENDED ACCESSORIES
IR MINI DOME		H4W2PER3	2 MP WDR IR Rugged Mini Dome Camera, PoE 802.3af or 12 VDC	IP66 rated IK10 vandal resistant	Smart IR, up to 98ft (30 m)	2.8mm fixed, F2.0	Junction Box: HQA-BB2; Wall Mount: HQA-WK; Pole Mount: HQA-PM2; Corner mount: HB34S2-CM; Rainshield: HQA-RS
		H4W4PER3	4 MP WDR True Day/Night IR Rugged Mini-Dome Camera, PoE 802.3af or 12 VDC		Smart IR, up to 82ft (25 m)		
		H4W2PER2	2 MP WDR True Day/Night IR Rugged Mini-Dome Camera, PoE 802.3af or 12 VDC		Smart IR, up to 98ft (30 m)	2.7 – 13.5mm, MFZ, F1.4	
		H4W4PER2	4 MP WDR True Day/Night IR Rugged Mini-Dome Camera, PoE 802.3af or 12 VDC		Smart IR, up to 150ft (45 m)		
			H4W8PR2		8 MP (4K) WDR True Day/Night IR Rugged Mini-Dome Camera, PoE 802.3af or 12 VDC		
IR BULLET		HBD2PER1	2 MP DWDR True Day/Night IR Bullet Camera, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 98ft (30 m)	3.6mm fixed, F2.0	Junction Box: HBS2-BB, HEJB; Pole Mount: HQA-PM, HQA-PM2; Corner Mount: HB34S2-CM
		HBW2PER1	2 MP WDR True Day/Night IR Bullet Camera, PoE 802.3af or 12 VDC				
		HBW4PER1	4 MP WDR True Day/Night IR Bullet Camera, PoE 802.3af or 12 VDC				
		HBW4PGR1	4 MP WDR True Day/Night IR Bullet Camera, PoE 802.3af or 12 VDC		Smart IR, up to 164ft (50 m)	4mm fixed, F1.6	Junction Box: HQA-BB5
		HBW2PER2	2 MP WDR True Day/Night IR Bullet Camera, PoE 802.3af or 12 VDC		Smart IR, up to 197ft (60 m)	2.7 – 13.5mm, MFZ, F1.4	Junction Box: HBS2-BB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HBW4PER2	4 MP WDR True Day/Night IR Bullet Camera, PoE 802.3af or 12 VDC		Smart IR, up to 164ft (50 m)		
			HBW8PR2		8 MP (4K) WDR True Day/Night IR Bullet Camera, PoE 802.3af or 12 VDC	Smart IR, up to 197ft (60 m)	
PTZ DOME		HDZP252DI	2 MP 25x zoom True Day/Night, DWDR, 6 High Power IR LEDs, In/Outdoor PTZ Dome, PoE+ 802.3at 12 VDC	IP66 rated	Smart IR, up to 328ft (100 m)	4.8–120mm, MFZ, F1.6–F4.4	Junction Box: HDZJB; Pole Mount: HDZPMA; Wall Mount: HDZGM; Corner Mount: HDZCMA; Ceiling Mount: HDZCM1, HDZCM2, HDZCM3
		HDZP304DI	4 MP 30x Zoom True Day/Night, WDR, 4 High Power IR LEDs, Indoor/Outdoor PTZ Dome, PoE+ 802.3at 24VAC				

*Depending on scene reflectance

Performance Series 4K Embedded NVRs

The 4K Ultra HD Embedded NVRs from the new Honeywell Performance Focus Series offer a feature rich, flexible and affordable video solution. Its multitude of channel, hard drive and internal storage options makes Focus 4K ideal for completion of any application and offers all the benefits of a hassle-free integration with Performance IP, HDZ PTZ Series, and equIP® Series S IP cameras.

		PART NUMBER	RESOLUTION	DESCRIPTION	INTERNAL HDD	RECORDING RATE	REMOVABLE MEDIA
4CH		HEN04113	8 MP (4K) @ 1-15fps	H.265 4 CH NVR, 1 TB, 4 PoE	2 ports up to 16 TB	80Mbps	2 ports (1 USB3.0; 1 USB2.0)
		HEN04123		H.265 4 CH NVR, 2 TB, 4 PoE			
8 CH		HEN08123	6MP/5MP/4MP/3MP/1080p/720p @25/30fps	H.265 8 CH NVR, 2 TB, 8 PoE	200Mbps		
		HEN08143		H.265 8 CH NVR, 4 TB, 8 PoE			
16 CH		HEN16123	H.265 16 CH NVR, 2 TB, 16 PoE				
		HEN16143	H.265 16 CH NVR, 4 TB, 16 PoE				
		HEN16163	H.265 16 CH NVR, 6 TB, 16 PoE				

	PART NUMBER	RESOLUTION	DESCRIPTION	INTERNAL HDD	RECORDING RATE	REMOVABLE MEDIA	
8 CH	 HEN08144	12 MP/8 MP (4K) @ 1-15fps 6MP/5MP/ 4MP/3MP/ 1080p/720p — @25/30fps	H.265 8 CH NVR, 4 TB, 8 PoE	2 ports up to 16 TB	240 fps @ 1080p (320 Mbps)	2 USB Ports (1 x USB 2.0, 1 x USB 3.0)	
	 HEN16144		H.265 16 CH NVR, 4 TB, 16 PoE				
16 CH	 HEN16184		H.265 16 CH NVR, 8 TB, 16 PoE	4 ports up to 32 TB	480 fps @ 1080p (320 Mbps)		3 USB Ports (1 x USB 2.0, 2 x USB 3.0)
	 HEN16284		H.265 16 CH NVR, 8 TB, 16 PoE				
32 CH	 HEN16384		H.265 16 CH NVR, 8 TB, 16 PoE	8 ports up to 64 TB	960 fps @ 1080p (320 Mbps)	4 USB Ports (2 x USB 2.0, 2 x USB 3.0)	
	 HEN321124		H.265 32 CH NVR, 12 TB, 16 PoE	2 ports up to 16 TB		2 USB Ports (1 x USB 2.0, 1 x USB 3.0)	
64 CH	 HEN32284		H.265 32 CH NVR, 8 TB, 16 PoE	4 ports up to 32 TB	1920 fps @ 1080p (320 Mbps)	3 USB Ports (1 x USB 2.0, 2 x USB 3.0)	
	 HEN322164		H.265 32 CH NVR, 16 TB, 16 PoE				
	 HEN32384		H.265 32 CH NVR, 8 TB, 16 PoE	8 ports up to 64 TB		4 USB Ports (2 x USB 2.0, 2 x USB 3.0)	
	 HEN323164		H.265 32 CH NVR, 16 TB, 16 PoE				
64 CH	 HEN643164		H.265 64 CH NVR, 16 TB, 16 PoE	8 ports up to 64 TB	1920 fps @ 1080p (320 Mbps)	4 USB Ports (2 x USB 2.0, 2 x USB 3.0)	
	 HEN643324		H.265 64 CH NVR, 32 TB, 16 PoE				
	 HEN643484	H.265 64 CH NVR, 48 TB, 16 PoE					



























Compatible Accessories

Honeywell's new Rack Mount Tray is compatible with both Embedded NVRs (HEN models) and Performance Series DVRs (HRHT and HRHQ models).

PART NUMBER	DESCRIPTION
HEN48VPS4CH	48 VDC 4CH HEN NVR Power Adapter (as replacement)
HENHQA12VPS	12V/5A HEN NVR & HQA DVR Power Adapter (as replacement)
HENHQARC	Remote Control, IR, for HEN NVR and HQA DVR (as replacement)
HENHQATRAY	ENVR & HQA DVR Rack Mount Tray
HEN4EC8	Performance 4K NVR Storage Expansion Chassis, 8 SATA (for HENxx2xx4 and HENxx3xx4 series)

Performance Series IP Kits

Honeywell's IP Kits come in a variety of configurations ranging from 4 and 8 Channel eNVRs and Bullet, Dome, and Ball Cameras.






		PART NUMBER	DESCRIPTION	
IP KITS	 x1	 x6	HEN8264D H.265 8-Channel 2 TB eNVR (HEN08123) with (6) 4MP Dome Cameras (H4W4PER3)	
	 x1	 x6	HEN8262T H.265 8-Channel 2 TB eNVR (HEN08123) with (6) 2MP Ball Cameras (HED2PER3)	
	 x1	 x4	HEN8242D H.265 8-Channel 2 TB eNVR (HEN08123) with (4) 2MP Dome Cameras (H4W2PER3)	
	 x1	 x4	 x2	HEN8224B44D H.265 8-Channel 2 TB eNVR (HEN08123) with (2) 4MP Bullet Cameras (HBW4PER1), (4) 4MP Domes Cameras (H4W4PER3)
	 x1	 x6	HEN8262B H.265 8-Channel 2 TB eNVR (HEN08123) with (6) 2MP Bullet Cameras (HBD2PER1)	
	 x1	 x4	 x2	HEN8222B42T H.265 8-Channel 2 TB eNVR (HEN08123) with (2) 2MP Bullet Cameras (HBD2PER1) and (4) 2MP Ball Cameras (HED2PER3)
	 x1	 x4	HEN4242D H.265 4-Channel 2 TB eNVR (HEN04123) with (4) 2MP Dome Cameras (H4W2PER3)	
	 x1	 x4	HEN4242T H.265 4-Channel 2 TB eNVR (HEN04123) with (4) 2MP Ball Cameras (HED2PER3)	
	 x1	 x2	 x2	HEN4224B24D H.265 4-Channel 2 TB eNVR (HEN04123) with (2) 4MP Bullet Cameras (HBW4PER1) and (2) 4MP Dome Cameras (H4W4PER3)
	 x1	 x2	 x2	HEN4222B22T H.265 4-Channel 2 TB eNVR (HEN04123) with (2) 2MP Bullet Cameras (HBD2PER1) and (2) 2MP Turret Cameras (HED2PER3)
 x1	 x4	HEN4242B H.265 4-Channel 2 TB eNVR (HEN04123) with (4) 2MP Bullet Cameras (HBD2PER1)		





Performance Series Mounts

The Performance Series IP offers a variety of multi-compatible Wall, Pole and Corner Mounts and Junction boxes.

		PART NUMBER	DESCRIPTION	COMPATIBLE CAMERAS
MOUNTS		HQA-BB1	Junction Box, Off-White	HEW2PER3, HEW2PER3B, HED2PER3, HEW4PER3 HBW2PR1, HBW4PR1, HBD8PR1
		HQA-BB2 HQA-BB2G	Junction Box, Off-White/Grey	H4W2PER3, H4W4PER3, H4W2PER2, H4W4PER2, H4W8PR2, HFD5PR1 H4D3PRV2, H4W2PRV2, H4W4PRV2, H4W4PRV3, HEW2PR2, HEW4PR2, H4D8PR1
		HQA-BB3 HQA-BB3G	Junction Box, Off-White/Grey	HEW2PER3, HEW2PER3B, H2W2PER3, H2W4PER3, H2W2PC1M H2W2PRV3, H2W4PRV3, HEW2PR1, HEW2PRW1, HEW3PR3, HEW4PRW3, HED8PR1
		HQA-BB4	Junction Box, Off-White	H4W2PER2, H4W4PER2, H4W8PR2
		HQA-BB5	Junction Box, Off-White	HBW4PGR1
		HBS2-BB	Junction Box, Off-White	HBD2PER1, HBW4PER1, HBW2PER2, HBW4PER2, HBW8PR2, HEW2PER2, HEW4PER2/B HED1PR3, HED3PR3, HBD1PR1, HBD3PR1, HBD3PR2, HBW2PR2, HBW4PR2
		HEJB	Junction Box, Off-White	HBD2PER1, HBW4PER1, HEW2PER2, HEW4PER2, HEW4PER2B HED1PR3, HED3PR3, HBD1PR1, HBD3PR1, HBD3PR2
		HQA-WK HQA-WKB	Wall Mount, Off-White/Grey	H4W2PER3, H4W4PER3, H4W2PER2, H4W4PER2, H4W8PR2, HEW2PER2, HEW4PER2, HEW4PER2B, HFD5PR1 HED1PR3, HED3PR3, H4D3PRV2, H4D3PRV3, H4W2PRV2, H4W4PRV2, H4W4PRV3, HEW2PR2, HEW4PR2, H4D8PR1
		HQA-WK2 HQA-WK2G	Wall Mount, Off-White/Grey	HED2PER3, HEW4PER3, HEW2PER3, HEW2PER3B H2W2PRV3, H2W4PRV3, HEW2PR1, HEW2PRW1, HEW4PR3, HEW4PRW3, HED8PR1
		HQA-PM2 HQA-PM2B	Pole Mount, Off-White/Grey	Compatible Junction Box: HQA-BB1, HQA-BB2, HQA-BB2G, HQA-BB3, HQA-BB4, HBS2-BB Compatible with Wall Mount: HQA-WK, HQA-WKB, HQA-WK2, HQA-WK2G
		HB34S2-CM HB34S2-CMB	Corner Mount, Off-White/ Grey	Compatible Junction Box: HQA-BB1, HQA-BB2, HQA-BB2G, HQA-BB3, HQA-BB4, HBS2-BB

* A compatible junction box is required when installing the HQA-PM2/B pole mount or the HB34S2-CM/B corner mount

		PART NUMBER	DESCRIPTION
PTZ ACCESSORIES		HDZPMA	Pole mount adapter for wall mount
		HDZCMA	Corner mount adapter for wall mount
		HDZJB	Junction box
		HDZNPTA	1.5" NPT adapter
		HDZWM2	Wall mount with access hole

		PART NUMBER	DESCRIPTION
PTZ ACCESSORIES		HDZGM	Wall mount gooseneck bracket
		HDZCM1	Ceiling mount
		HDZCM2	Ceiling mount extension pole for HDZCM1, 220 mm
		HDZCM3	Ceiling mount extension pole for HDZCM1, 420 mm

Performance Series High Quality Analog (HQA)

Hassle-Free HD Cameras

Honeywell's Performance Series HQA offers competitively priced cameras for everyday security applications from a partner you know and trust. Performance you want at the price you need.

PERFORMANCE SERIES HQA CAMERAS										
CAT.	PART NUMBER	DESCRIPTION	LENS	RESOLUTION	INPUT VOLTAGE	ANALOG FORMAT	IR ILLUMINATION*	ENVIRONMENT	RECOMMENDED ACCESSORIES	
IR BALL		HD30HD4	Indoor/Outdoor IR Ball, True Day/Night, True WDR	3.6 mm Fixed Lens	4 MP (2560 x 1440)	12 VDC	HD-CVI	Smart IR, up to 164 ft (50 m)	IP66	Wall Mount: HQA-WK2; Junction Box: HQA-BB3; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HE30XD2	Indoor/Outdoor IR Ball, True Day/Night	3.6 mm Fixed Lens	1080p (1920 x 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 130 ft (40 m)	IP66	Junction Box: HQA-BB3; Pole Mount: HQA-PM2; Wall Mount: HQA-WK
		HE30XD2G	Indoor/Outdoor IR Ball, True Day/Night	3.6 mm Fixed Lens	1080p (1920 x 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 130 ft (40 m)	IP66	Junction Box: HQA-BB3G; Pole Mount: HQA-PM2B; Wall Mount: HQA-WKB
		HE42XD2	Indoor/Outdoor IR Ball, True Day/Night, True WDR	2.7 -13.5 mm MFZ Lens	1080p (1920 x 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 164 ft (50 m)	IP66	Pole Mount: HQA-PM2; Wall Mount: HQA-WK
		HE42XD2G	Indoor/Outdoor IR Ball, True Day/Night, True WDR	2.7 -13.5 mm MFZ Lens	1080p (1920 x 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 164 ft (50 m)	IP66	Pole Mount: HQA-PM2B; Wall Mount: HQA-WKB
IR RUGGED DOME		HD72HD4	Rugged IR Dome, True Day/Night, True WDR	2.8 mm Fixed Lens	4 MP (2560 x 1440)	12 VDC	HD-CVI	Smart IR, up to 100 ft (30 m)	IP66, IK10	Wall Mount: HQA-WK; Junction Box: HQA-BB2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HD274HD4	Rugged IR Dome, True Day/Night, True WDR	2.7-12 mm MFZ Lens	4 MP (2560 x 1440)	12 VDC/24 VAC	HD-CVI	Smart IR, up to 100 ft (30 m)	IP66, IK10	Wall Mount: HQA-WK; Junction Box: HQA-BB2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HD42XD2	Rugged IR Dome, True Day/Night, True WDR	2.7 -13.5 mm MFZ Lens	1080p (1920 x 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 98 ft (30 m)	IP66, IK10	Wall Mount: HQA-WK; Pole Mount: HQA-PM2;
		H4D42HD8	IR Rugged Dome, True Day/Night, True WDR	3.7-11 mm MFZ Lens	4K (3840 x 2160)	12 VDC/24 VAC	HD-CVI	Smart IR, up to 98 ft. (30 m)	IP66, IK10	Junction Box: HQA-BB4 or HQA-BB2/G; Pole Mount: HQA-PM2; Wall Mount: HQA-WK; Pendant Mount: HQA-PK; In-Ceiling Bracket: HQA-IC; Ceiling Mount: HQA-CB; Rain Shield: HQA-RS
		HD30XD2	Indoor/Outdoor IR Rugged Dome, True Day/Night, True WDR	3.6 mm Fixed Lens	1080p (1928 x 1088)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 98 ft. (30 m)	IP66, IK10	Pole Mount: HQA-PM2; Wall Mount: HQA-WK; Junction Box: HQA-BB2/G; Corner Mount: HB34S2-CM; Rain Shield: HQA-RS
		HD41XD2	Indoor/Outdoor IR Rugged Dome, True Day/Night, True WDR	2.7-13.5 mm Vari-focal Lens	1080p (1928 x 1088)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 98 ft. (30 m)	IP66, IK10	Junction Box: HQA-BB4 or HQA-BB2/G; Pole Mount: HQA-PM2; Wall Mount: HQA-WK; Pendant Mount: HQA-PK; In-Ceiling Bracket: HQA-IC; Ceiling Mount: HQA-CB; Rain Shield: HQA-RS
		HD273XD2	Indoor/Outdoor IR Rugged Dome, True Day/Night, DWDR	2.8-12 mm Vari-focal Lens	1080p (1984 x 1105)	12 VDC/24 VAC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 131 ft. (40 m)	IP66, IK10	Wall Mount: HD273-WM; Pendant Mount: HD273-PK; In-Ceiling Bracket: HD273-IC



*Depending on scene reflectance

PERFORMANCE SERIES HQA CAMERAS

CAT.	PART NUMBER	DESCRIPTION	LENS	RESOLUTION	INPUT VOLTAGE	ANALOG FORMAT	IR ILLUMINATION*	ENVIRONMENT	RECOMMENDED ACCESSORIES
IR BULLET	 HB74HD4	Indoor/Outdoor IR Bullet, True Day/Night, True WDR	3.6 mm Fixed Lens	4 MP (2560 x 1440)	12 VDC	HD-CVI	Smart IR, up to 131 ft (40 m)	IP66	Junction Box: HQA-BB1; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
	 HB276HD4	Indoor/Outdoor IR Bullet, True Day/Night, True WDR	2.7-12 mm MFZ Lens	4 MP (2560 x 1440)	12 VDC / 24 VAC	HD-CVI	Smart IR, up to 200 ft (60 m)	IP66	Junction Box: HBS2-BB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
	 HB30XD2	Indoor/Outdoor IR Bullet, True Day/Night	3.6 mm Fixed Lens	1080p (1920 x 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 98 ft (30 m)	IP66	Junction Box: HBS2-BB, HEJB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
	 HB42XD2	Indoor/Outdoor IR Bullet, True Day/Night, True WDR	2.7-13.5 mm MFZ Lens	1080p (1920 x 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 164 ft (50 m)	IP66	Junction Box: HBS2-BB, HEJB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
	 HB30PHD2	Indoor/Outdoor IR Bullet, True Day/Night, True WDR	2.8 mm Lens	1080p (1928 x 1088)	12 VDC	HD-CVI	Smart IR, up to 82 ft (25m)	IP66	Junction Box: HBS2-BB or HEJB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
	 HBD42HD8	Indoor/Outdoor IR Bullet, True Day/Night, True WDR	3.7-11 mm MFZ Lens	4K (3840 x 2160)	12 VDC / 24 VAC	HD-CVI	Smart IR, up to 150 ft (50 m)	IP66	Junction Box: HBS2-BB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
	 HB41XD2	Indoor/Outdoor IR Bullet, True Day/Night, True WDR	2.7-13.5 mm Vari-focal Lens	1080p (1928 x 1088)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 98 ft (30 m)	IP66	Junction Box: HBS2-BB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
PTZ	 HDP302DQI	1080p 30x IR PTZ Dome (Wall Mount Bracket Included)	4.5-135.0 mm Lens, 30x Optical Zoom	1080p (1920 x 1080)	24 VAC	HD-CVI	Smart IR, up to 492 ft (150 m)	IP66	Junction Box: HDZJB; Pole Mount: HDZPMA; Corner Mount: HDZCMA; Ceiling Mount: HDZCM1
	 HDZP30XD4	4 MP 30x IR PTZ Dome (Wall Mount Bracket Included)	4.5-135.0 mm Lens, 30x Optical Zoom	4 MP (2592 x 1520)	24 VAC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 328 ft (100 m)	IP66	Junction Box: HDZJB; Pole Mount: HDZPMA; Corner Mount: HDZCMA; Ceiling Mount: HDZCM1; Mount Adapter: HDZBSPPA
FISHEYE	 HFD40HD4	Fisheye, True Day/Night, WDR	1.18 mm Fixed Lens	4 MP (2560 x 1440)	12 VDC	HD-CVI	NA	IK10	Junction Box: HQA-BB2/G; Pole Mount: HQA-PM2; Wall Mount: HQA-WK; Corner Mount: HB34S2-CM; Pendant Mount: HQA-PK;

*Depending on scene reflectance




PERFORMANCE SERIES ANALOG CAMERAS

CAT.	PART NUMBER	DESCRIPTION	LENS	RESOLUTION	INPUT VOLTAGE	ANALOG FORMAT	IR ILLUMINATION*	ENVIRONMENT	RECOMMENDED ACCESSORIES
DOME	 HD262H	Indoor IR Mini Dome, True Day/Night	2.8-12 mm, F1.4, VFMI	700 TVL	12 VDC / 24 VAC ±10%	960H	Smart IR, up to 66 ft (20 m)	N/A	Wall Mount: HDPR1-WM; Pendant Mount: HD262H-PK; In-Ceiling Mount: HD262H-IC
IR RUGGED DOME	 HD273H	Rugged IR Mini Dome, True Day/Night	2.8-12 mm, F1.4, VFMI	700 TVL	12 VDC / 24 VAC ±10%	960H	Smart IR, up to 100 ft (30 m)	IP66, IK10	Wall Mount: HD273H-WM; Pendant Mount: HD273H-PK; In-Ceiling Mount: HD273H-IC;

*Dependence on scene reflectance

DVRs

Our digital video recorders support a wide variety of user-friendly capabilities such as mouse operation, IR remote control, remote connectivity and best-in-class search engines.







PERFORMANCE SERIES HQA DVRs				
CAT.		PART NUMBER	DESCRIPTION	STORAGE
4 CH		HRHT4041	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 1HDD-bay High/Standard Definition Analog Hybrid	1 TB
		HRHT4042	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 1HDD-bay High/Standard Definition Analog Hybrid	2 TB
		HRHQ1041	1080p 15fps/ch (720p 25/30 fps/ch) DVR 1HDD-bay High/Standard Definition Analog Hybrid	1 TB
8 CH		HRHT4082	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	2 TB
		HRHT4084	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	4 TB
		HRHQ1081	1080p 15fps/ch (720p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	1 TB
		HRHQ1082	1080p 15fps/ch (720p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	2 TB
16 CH		HRHT4162	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	2 TB
		HRHT4164	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	4 TB
		HRHT4166	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	6 TB
		HRHT41612	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	12 TB
		HRHQ1162	1080p 15fps/ch (720p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	2 TB
		HRHQ1164	1080p 15fps/ch (720p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	4 TB

Performance Series HQA Kits

Honeywell's HQA Kits come in a variety of configurations ranging from 4, 8 and 16 Channel Hybrid DVRs and Bullet, Dome, and Ball Cameras.

		PART NUMBER	DESCRIPTION
IP KITS	 x1	 x4	HQA4142T 4-Channel 1TB DVR (HRHQ1041) with (4) 2MP Ball Cameras (HE30XD2)
	 x1	 x4	HQA4244T 4-Channel 2TB DVR (HRHT4042) with (4) 4MP Ball Cameras (HD30HD4)
	 x1	 x6	HQA8262T 8-Channel 2TB DVR (HRHQ1082) with (6) 2MP Ball Cameras (HE30XD2)
	 x1	 x6	HQA8464T 8-Channel 4TB DVR (HRHT4084) with (6) 4MP Ball Cameras (HD30HD4)
	 x1	 x6	HQA8262D 8-Channel 2TB DVR (HRHQ1082) with (6) 2MP Dome Cameras (HD30XD2)
	 x1	 x6	HQA8464D 8-Channel 4TB DVR (HRHT4084) with (6) 4MP Dome Cameras (HD72HD4)
	 x1	 x6  x6	HQA16462T62D 16-Channel 4TB DVR (HRHQ1164) with (6) 2MP Ball (HE30XD2) and (6) 2MP Dome Cameras (HD30XD2)
	 x1	 x6  x6	HQA16664T64D 16-Channel 6TB DVR (HRHT4166) with (6) 4MP Ball (HD30HD4) and (6) 4MP Dome Cameras (HD72HD4)

CAT.	PART NUMBER	DESCRIPTION	COMPATIBLE CAMERAS
MOUNTS	 HQA-WK HQA-WKB	Wall Mount, Off-White/Grey	HD29HD1, HD31HD2, HD231HD2, HD73HD1, HD74HD2, HD274HD2, HD72HD4, HD274HD4, HD42XD2, HE30XD2/G, HE42XD2/G
	 HQA-WK2/ HQA-WK2G	Wall Mount, Off-White/Gray	HD30HD1, HD30HD2, HD30HD4
	 HQA-BB1	Junction Box, Off-White	HD30HD1, HD30HD2, HB74HD2, HB74HD4
	 HQA-BB2/ HQA-BB2G	Junction Box, Off-White/Gray	HD72HD4, HD274HD4, HD31HD2, HD73HD1, HD74HD2, HD231HD2, HD274HD2
	 HQA-BB3/ HQA-BB3G	Junction Box, Off-White/Gray	HD30HD4, HE30XD2, HE30XD2G
	 HEJB	Junction Box, Off-White	HD31HD2, HD231HD2, HB74HD1, HB30XD2, HB42XD2
	 HBS2-BB	Junction Box, Off-White	HD29HD1, HD31HD2, HD231HD2, HB74HD1, HB75HD1, HB76HD2, HB276HD2, HB276HD4, HB30XD2, HB42XD2
	 HQA-PM2* HQA-PM2B*	Pole Mount, Off- White/Grey	All Performance Series HQA cameras (with a compatible junction box), except PTZ cameras
	 HB34S2-CM* HB34S2-CMB*	Corner Mount, Off-White/Grey	All Performance Series HQA cameras (with a compatible junction box), except HE30XD2/G, HE42XD2/G, HD42XD2 and PTZ cameras

CAT.	PART NUMBER	DESCRIPTION	COMPATIBLE CAMERAS
MOUNTS	 HQA-BB4	Junction Box, Off-White	H4D42HD8, HD274HD4, HD41XD2, HD42XD2
	 HQA-IC	In-Ceiling Bracket, Off-White	H4D42HD8, HD274HD4, HD41XD2, HD42XD2
	 HQA-RS	Rain Shield Bracket, Off-White	H4D42HD8, HD274HD4, HD41XD2, HD42XD2, HD30XD2, HD72HD4
	 HQA-PK	Pendant Mount Cap, Off-White	All HQA cams models except Bullet models
	 HQA-CB	Ceiling Mount Bracket, Off-White	All HQA cams models except Bullet models
	 HQA-CBE	Ceiling Mount extension for HQA-CB, Off- White	All HQA cams models except Bullet models

* With a compatible junction box (please refer to the Mount data sheet at www.honeywellvideo.com)



FoV calculator



NVR Bandwidth Calculator



Bracket Compatibility table



Cameras & NVRs Interactive
Presentation

Download the tools on www.honeywellvideo.com



Extended warranty
on select cameras



Over the counter exchange
on defective product



Add RMR to every surveillance
proposal, sale and installation



Cloud Service enabled
helps you drive RMR

Honeywell Security and Fire

2700 Blankenbaker Pkwy, Suite 150
Louisville, KY 40299
1.800.323.4576
www.honeywell.com

HSV-PERF-01-US(0119)DS-Z
2019 Honeywell International Inc.

