

DS-1600KI

Network Keyboard



The Hikvision DS-1600KI network keyboard is a 4-axis joystick control device. It features a 10.1" capacitive touchscreen, and supports DVI and HDMI video output.

The DS-1600KI runs on a Android operating system, and supports a wide range of Hikvision front and back-end devices.

Available models:

DS-1600KI

- 10.1" Capacitive Touchscreen
- Detachable Touchscreen and Joystick Design
- Wired and WiFi Network Connection
- PoE Power Supply
- Up to 2-ch 1080p Decoding; 16-Division Window Display
- DVI and HDMI Monitor Output
- Connectable to Hikvision Products, such as DVRs, DVSs, NVRs, Network Cameras, and Speed Domes

Specifications

DS-1600KI	
System	
TFT LCD Screen	10.1" TFT LCD touchscreen 1024 x 600 pixel screen
Joystick	4-axis joystick
Local Decoding	Local live view at 1080P/720P/HD1/BCIF/CIF/QCIF resolution, and up to 16-division window display
External Interfaces	
Network Interface	1-port 10M/100M/1000M Adaptive Ethernet port
Two-Way Audio Input	1-ch, 3.5mm connector (2.0 Vp-p, >1 kΩ)
Audio Output	1-ch, 3.5mm connector (2.0 Vp-p, 600 Ω)
Wi-Fi	Supported
USB Interface	USB 2.0 × 2
Video Interface	HDMI, DVI
General	
Power Supply	12 VDC/PoE
Consumption	≤15 W
Working Temperature	14° F to 131° F (-10° C to 55° C)
Working Humidity	10% to 90%
Dimensions (W x D x H)	404 mm × 180 mm × 163 mm (15.9" × 7.1" × 6.4")
Weight	1.7 kg (3.75 lb)