

## ECT-T32V2

### 2 MP Outdoor EXIR VF Turret Camera

**TurboHD™**



- 2 MP High Performance CMOS
- Up to 1920 x 1080 Resolution
- 2.8 mm to 12 mm Manual Vari-Focal Lens
- EXIR 2.0 up to 130 ft (40 m) IR Range
- Smart IR
- DWDR, BLC
- Multi-Protocol Output:  
TVI/AHD/CVI/CVBS
- IP66 Protection

The Hikvision ECT-T32V2 Outdoor EXIR VF Turret Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

EXIR 2.0 is Hikvision's proprietary IR extended range technology, which has a range of 130 feet (40 meters).

The 2.8 mm to 12 mm manual vari-focal lens is optimized for viewing angles that fit any situation.

**Available models:**  
ECT-T32V2



# Specifications

ECT- T32V2	
<b>Camera</b>	
Image Sensor	2 MP CMOS image sensor
Signal System	NTSC
Effective Pixels	1920 (H) x 1080 (V)
Minimum Illumination	0.01 Lux @ (f1.2, AGC on), 0 Lux with IR
Shutter Speed	1/25 (1/30) s to 1/50,000 s
Lens	2.8 mm to 12 mm manual vari-focal lens
Horizontal Field of View	111.5° to 33.4°
Lens Mount	Ø 14
Day / Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Synchronization	Internal synchronization
Video Frame Rate	1080p @ 30 fps
<b>Menu</b>	
AGC	High/medium/low/off
D/N Mode	Auto/color/BW (black and white)
BLC	Supported
DWDR	Supported
Language	English
Functions	Brightness, sharpness, DNR, mirror, smart IR
<b>Interface</b>	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
<b>General</b>	
Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25%
Power Consumption	Maximum 4.8 W
Protection Level	IP66
Material	Enclosure: plastic; main body: metal
IR Range	Up to 130 ft (40 m)
Dimensions	Ø 4.72" x 4.16" (Ø 120 mm x 105 mm)
Weight	Approximately 0.99 lbs (450 g)

# Accessories

						
<b>WML + PC130T</b> Wall Mount Long + 130 mm Pendant Cap	<b>PM</b> Pole Mount	<b>CM</b> Corner Mount	<b>CPM + PC130T</b> Ceiling Pendant Mount + 130 mm Pendant Cap	<b>CBM</b> Conduit Base	<b>ABS</b> 15° Angled Base	<b>CBT-1</b> Conduit Base

# Dimensions

