

## DS-K170HPK

### Proximity Mullion-Mount Reader and Keypad



Hikvision proximity card readers set the electronic security benchmark for 125 kHz proximity readers, cards, and tags.

Based upon proven contactless digital radio frequency identification (RFID) technology, proximity readers interact with a wide range of electronic access control systems by complying with the Wiegand communication protocol.

#### Available Models:

DS-K170HPK

- Independently Tested and Certified to Conform to UL Standard 294
- Wiegand Interface
- Mullion Mount for Metal Doors, Window Frames, and Flat Surfaces
- Up to 5 inches (126 mm) 125 kHz Reading Frequency

# Specifications

DS-K170HPK	
System Parameters	
Technology	Proximity
Reading Frequency	125 kHz
Reading Range	Up to 5 inches (126 mm)
Interface	Wiegand 26
Keypad Output	Wiegand
LED	Four-state standard (red, green, amber, and off)
Mounting	Mullions, including metal doors and window frames, as well as flat surfaces
Dimensions (W x H x D)	1.78" x 6.1" x 0.91" (45 mm x 155 mm x 23 mm)
Weight	4 oz (113 g)
Certifications	FCC, ICC, CE, C-Tick, UL Standard 294 ETL Listed
IP Code	IP67
Power Supply	5 to 16 VDC
Working Current	70 mA typical, 110 mA peak @ 12 VDC
Cabling	24 AWG minimum, multi-conductor stranded with an overall foil shield
Operating Temperature	-40° to 149° F [-40° to +65° C]
Color Options	Black snap-on cover included standard
Audio Tone	Beeper included standard
Indoor and Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting

# Legend and Dimensions

**Shown Actual Size**

To use as a template for mounting on flat surfaces, print page at 100% (Letter)

