

## DS-K7M153-P Proximity Key Fob



- 125 kHz Frequency
- Standard Reinforced Brass Eyelet
- Up to 3.5" (88 mm) Read Range
- 25 Key Fobs Included

Hikvision proximity key fobs set the electronic security benchmark for 125 kHz proximity readers, cards, and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, Hikvision proximity key fobs interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol.

Additionally, proximity key fobs are passive devices and eliminate the need for maintenance by requiring no batteries, and can be ordered to support several proximity reader technologies.

**Available Models:**

DS-K7M153-P

# Specifications

DS-K7M153-P	
System Parameters	
Technology	Proximity
Frequency	125 kHz
Operation	Passive (no battery)
Type	Key fob
Formats	Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)
Material	ABS
Color	Gray
Slot Punch	Standard reinforced brass eyelet
Read Range	Up to 3.5" (88 mm)
Single Key Fob Dimensions	1.2" W x 1.5" H x 0.15" D (30 mm x 38 mm x 3.8 mm)
Shipping Dimensions (25 Key Fobs)	3.5" W x 2.3" H x 1.8" D (88 mm x 57 mm x 46.8 mm)
Weight	Single key fob: 0.12 oz (3.6 g) Box of 25 key fobs: 0.2 lbs (90.7 g)
Operating Temperature	-35° to 122° F (-37° to 50° C)
Humidity	0% to 95% (non-condensing)