EN4080 IP Gateway





The EN4080 IP gateway combines the functionality of an Inovonics EN4000 receiver with the flexibility of an IP appliance. With a message queuing telemetry transport (MQTT) license, the IP gateway outputs messages in the MQTT protocol; with a BACnet/ IP license, the IP gateway outputs messages in the BACnet/IP protocol.

Product Features

Optional Power over Ethernet (PoE) feature

Supports over-the-air updates

MQTT license compatible with all Inovonics transmitters; BACnet license compatible with Inovonics environmental, pulse counting and select security transmitters

External LEDs indicate power, IP connectivity and message receipt

Product Specifications

| Weight: | 1 lb. 3.54 oz |
|------------------------------------|--|
| Dimensions: | 9.556" x 6.65" x 1.208" |
| Power requirement: | Line power: The Inovonics ACC610 transformer, or a 12-14V AC intrinsically safe power supply capable of supplying at least 16W, or a 12-15V DC power supply capable of supplying at least 15W; POE: IEEE 802.3af- 2003 compliant |
| Router requirements: | The router may assign addresses via DHCP; the DHCP lease of the router must be set to a non-zero and non-infinite value, and should be set to a value greater than 30 seconds; the router must allow outbound connections on the following ports: DNS (53/TCP+UDP), HTTPS (443/TCP), NTP (123/UDP), OTA (9000/TCP) |
| Connectivity: | Ethernet: 10/100Base-T, DHCP, static IP; WiFi: 802.11b/g/n, 2.4GHz, WPA/2-Personal, DHCP, static IP |
| Storage capacity: | Messages for 150 transmitters for 30 days, reporting in at 15 minute intervals, or equivalent |
| Operating environment: | |
| Temperature: | 32°F to 140°F (0°C to 60°C) |
| Humidity: | Up to 90% (non-condensing) |
| Market: | North America, Australia, New Zealand |
| EchoStream [®] frequency: | 902-928 MHz, frequency hopping spread spectrum |
| Check-in time frequency: | 3 minutes |
| Regulatory compliance: | FCC part 15 class B, ISED, RCM, RoHS |
| | |

Reference Materials (available at www.inovonics.com)

EN4080 IP Gateway Installation Instructions

E*4080 IP Gateway Amazon Web Services MQTT Quick Start Tech Note

E*4080 IP Gateway BACnet/IP Quick Start Tech Note

Inovonics Product Catalog: North America

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.
- Inovonics supports recycling and reuse whenever possible. Please recycle these parts using a certified electronics recycler.

Technical documents

For technical documents visit us at http://www.inovonics.com/support/ tech-documents/ or use the QR code below.



Inputs



