Product Specifications



3 oz Clear RTV Silicon Sealant

Part number RTV3

Category number 6200

UPC 781002173601

The RTV3 is a high quality, single component, 100% silicone sealant that is ideal for interior and exterior sealing and caulking. It adheres to metal, glass, marble, tile ceramic, porcelain, painted surfaces, and many more. It can be used as an adhesive for bonding surfaces together and will not yellow or discolor in exterior applications.



Physical Characteristics

| Туре | Silicon Sealant |
|-------|-----------------|
| Color | Clear |

Packaging Details

| Container | Tube |
|----------------|------|
| Standard Qty | 1 |
| Master Qty | 12 |
| Price Per | 1 |
| Package Length | 8.00 |
| Package Width | 3.90 |
| Package Height | 0.10 |
| Package Weight | 0.28 |
| | |

Performance Data

| Elongation 5 Temperature Range (F) -62°F to 450° Special Features Watertight, Low Odor, Flexible, Will Not Crack, Shrink or Peel, UV Resistant, Remains Flexible, Multi-Purpose, Excellent Adhesion to a Variety of Surfaces Tack-Free Time 20 Minute | | |
|---|-----------------------|---------------------|
| Temperature Range (F) -62°F to 450° Special Features Watertight, Low Odor, Flexible, Will Not Crack, Shrink or Peel, UV Resistant, Remains Flexible, Multi- Purpose, Excellent Adhesion to a Variety of Surfaces Tack-Free Time 20 Minute | Tensile Modulus | 4 MPa |
| Special Features Watertight, Low Odor, Flexible, Will Not Crack, Shrink or Peel, UV Resistant, Remains Flexible, Multi- Purpose, Excellent Adhesion to a Variety of Surfaces Tack-Free Time 20 Minute | Elongation | 5.5 |
| . Watertight, Low Odor, Flexible, Will Not Crack, Shrink or Peel, UV Resistant, Remains Flexible, Multi- Purpose, Excellent Adhesion to a Variety of Surfaces Tack-Free Time 20 Minute | Temperature Range (F) | -62°F to 450°F |
| Purpose, Excellent Adhesion to a Variety of Surfaces Tack-Free Time 20 Minute | Special Features | |
| 20 Williage | | ns Flexible, Multi- |
| Specific Gravity 1.04 @ 77° | Tack-Free Time | 20 Minutes |
| | Specific Gravity | 1.04 @ 77°F |

Certifications

| RoHS Compliant | Yes |
|--------------------|-----------|
| Industry Standards | UL Listed |

Meets/Exceeds

USDA For Use In Federally Inspected Meat/Poultry Plants, F.D.A. Reg. #21 CFR 177.2600, TT-S-001543A (COM-NBS) Class A, TT-S-00230C (COM-NBS) Class A And Canadian 19-GP-9MA Type 1, Conforms to NSF standard 51

L.H. Dottie Co. Commerce, CA 323-725-1000 www.lhdottie.com