



Model NV-652R Video Receiver



Features:

- Full-motion CCTV video at distances up to 3,000ft (1km) when used with any passive NVT transceiver; 1 mile (1,6km) when used with NV-653T transmitter
- Exceptional interference rejection
- Built-in transient protection and ground lifting
- Built-in brightness and sharpness controls; blue power LED, green active LED
- Compatible with qualified UTP cameras
- Up to ten NV-652Rs may be rack mounted using the NV-RM8/10 rack panel kit
- Best choice for DVR and high resolution applications over 750ft (225m)
- Limited lifetime warranty

The NVT Model NV-652R Video Receiver is an active (amplified) device that allows the transmission of real-time mono-chrome or color video on up to 1 mile (1,6km) using Category Unshielded Twisted-Pair (UTP) telephone wire.

The unparalleled interference rejection and low emissions of the Model NV-652R allow long run video signals to co-exist in the same wire bundle as telephone, datacom, or low-voltage power circuits. This allows the use of shared or existing cable plant. Ground-lifting ensures no annoying “hum-bars” when ground potential differences exist. With built-in transient protection, damaging voltage spike problems are eliminated. The built-in sharpness and brightness controls compensate for cable loss.

Network Video Technologies

4005 Bohannon Drive • Menlo Park, CA 94025 • USA
(+1) 650.462.8100 • FAX (+1) 650.326.1940
nvt.com • www.nvt.com/email




Model NV-652R

Video Receiver

Technical Specifications

VIDEO DISTANCE RECOMMENDATIONS



VIDEO

Frequency response	DC to 10 MHz
Adjustable brightness and sharpness controls	
Common-mode / Differential-mode rejection	
15 KHz to 5 MHz	60 dB typ
Impedance	
Coax, female BNC	75 ohms
UTP, Screw terminal block	100 ohms

LED INDICATORS

Blue "Power-On"; Green "Active" signal present

WIRE TYPE

Network Wiring	One Unshielded Twisted Pair
	24-16 AWG (0.5-1.31mm)
Category Type	2 or better
Impedance	100 ± 20 ohms
DC Loop Resistance	52 ohms per 1,000ft (18 ohms per 100m)
Differential Capacitance	19 pF/ft max (62 pF/m max)

POWER

12 - 24VAC / DC (transformer not included) 100 mA max
One floating power supply may power multiple NV-652R Receivers

ENVIRONMENTAL

Ambient temperature	+32 to +122°F (0 to +50 °C)
Humidity (non-condensing)	0 to 95%
Transient Immunity	per ANSI / IEEE 587 C62.41

MECHANICAL


Dimensions, excluding brackets and connectors	3.00 x 1.54 x 1.10in (76 x 39 x 28mm)
Packaged weight	4.0oz (100g)
Material	Black ABS
Mounting	Two 0.175 in (4,4mm) diameter holes 2.5in (63,5mm) apart

Up to ten NV-652Rs can be mounted to an NV-RM 8/10 Rackmount Panel

Specifications subject to change without notice.

Typical Application

Passive to Active Application up to 3,000ft (1km)



Active to Active Application up to 1 mile (1,6km)

