

AeGIS 7000C SERIES

MULTI-TENANTS CELLULAR TELEPHONE ENTRY SYSTEM



250 tenants and 250 codes

Single relay

Large LCD for easy reading

Postal lock ready

Backlit Keypad

Brushed stainless steel, dark gray powder coated back box

Surface and Flush Mount.

Outdoor or Indoor

24 months warranty

FEATURES	PART#: 7000C (Surface Mount)	PART#: 7000CFF (Flush Mount)
Input Power (Telephone Entry)	12VAC included/12VDC	12VAC included/12VDC
Total Current Consumption	1700 mA	1700 mA
Operating Temperature	10°F to 145°F	10°F to 145°F
LiquidCrystal Display	16 x 1, 99mm x 13mm	16 x 1, 99mm x 13mm
Tenant Capacity	250	250
Code Capacity	250	250
Remote Access	yes	yes
SCWT65 4G-LTE GSM Cellular	included, outdoor or indoor 12VAC 40VA	included, outdoor or indoor 12VAC 40VA
4G-LTE GSM Cellular	AT&T	AT&T
Dry Contact Relay	1	1
Postal Lock Ready	yes	yes
Auxiliary Input	1	1
Telephone Entry Dimension (HWD)	10-13/16" x 8-5/8" x 3-3/4"	14-5/16" x 12-1/8" x 2-5/8" (Total Dimension) 11-1/8" x 8-11/16" x 2-5/8" (Inside Ring)
SCWT65 Dimension	12-3/5" (H) x 9-1/2" (W) x 4-3/10" (D)	

ACCESSORIES

UVPC: Analog color camera	UPM1L: 47" H Single arm pedestal
USP1: AC and Telephone surge protector	UPM2: Dual vertical arm pedestal
USP2L: Surge and Lightning protection	UPM5: Dual horizontal arm pedestal
UBAT1: 12VDC 4.5 Ahr backup battery (Telephone Entry Only)	UPM6L: 64" H Single arm pedestal
IREXIT: Infrared exit switch	AHP5: Heater-pad
78SHLD: Sun Shield for Telephone Entry	

PACH AND COMPANY INC.
CALIFORNIA ■ 949-498-2951 ■ 1-888-678-7224