



## ADSPOT

### SINGLE POSITION OUTDOOR POWER SUPPLY

#### SPECIFICATIONS

##### Model Number

ADSPOT .....240 VAC (field changeable to 120 VAC)  
Transformer jumpers are field changeable to support either 120 VAC or 240 VAC

ADSPOT is used with any American Dynamics dome or fixed camera

##### Electrical

Power Source .....100-120 VAC or 200-240 VAC @ 50/60 Hz  
Operational Limits .....90-135 VAC or 180-265 VAC @50/60 Hz  
Input Current .....1.0A/0.5A  
Output .....24 VAC, 2.5A max.  
UL Listed Class 2  
Certified Limited Power Source

##### Mechanical

Dimensions (H x W x D) .....175 x 125 x 75 mm  
(6.9 x 4.9 x 3.0 in)  
Weight .....3.7 kg (8.2 lbs)  
Enclosure Material .....Impact-resistant polycarbonate  
Color .....Light gray  
Wall Mounting Options .....Concrete, wood or sheet rock  
Mounting Area (H x W) .....281 x 200 mm  
(11.1 x 7.9 in)  
Cover Fasteners .....Four captive screws  
Cable Access Knockouts .....Eight 21 mm or 15.5 mm  
(0.83 in or 0.61 in)  
Four 29 mm or 23 mm  
(1.14 in or 0.91 in)

##### Environmental

Weatherproof Standard .....NEMA 4, IP66  
Operating Temperature .....-40° to 50° C (-40° to 122° F)  
Storage Temperature .....-40° to 50° C (-40° to 122° F)  
Humidity .....0% to 95% RH (non condensing)

##### Regulatory

Safety .....UL 60950  
CSA C22.2 No. 60950  
EN60950  
IEC 60950

Product specifications and availability subject to change without notice.  
Certain product names mentioned herein may be trade names and/or registered trademarks of other companies.



This weather-tight box provides Class 2 LPS power to the SpeedDome® Ultra and SpeedDome Optima outdoor camera housings. It is designed for use in the harshest of outdoor environments.

- Supports both 120 VAC and 230 VAC
- Weatherproof design: NEMA 4 and IP66 rated
- Small, compact design
- Euro-style terminal blocks make for quick and simple installation