

# RCI 912 Series

## Touch-free actuators



## Wireless, battery power, touch-free actuators come with infrared motion detection technology

The RCI 912 Series wireless, battery power, actuators utilize proven infrared motion detection technology to ensure consistent, dependable touch-free activation and can be adjusted to comply with ANSI knowing act applications.

The 912 Series is available in three models (with or without receivers) including for glass wall or smooth surface applications. The 912 actuator detects moving objects such as a hand, reflective object, cart, or wheelchair and relays a signal to a receiver triggering an automatic door opener. It is ideal for use in hospitals, pharmacies, clean rooms, food service facilities, and other applications requiring a hygienic touch free activation method.

### Features & Benefits

- Infrared Motion Detection Technology
- Touch Free Activation with hand or reflective object provides clean and hygienic activation (less than 130 ms).
- Silent activation for hospitals and other noise-sensitive environments
- 2.4Ghz transmitter and receiver (line of site +30 meters/100ft)
- Detection distance is adjustable from 3~30 cm (1"-12")
- SPDT relay output can be used for signaling/switching automatic doors and access control (3A @ 30VDC)
- Low power consumption providing long battery life (4"AA"-912, 2"AA"-912N, 2"AAA"-912GL). Batteries not included.
- Selectable activation output between 1.5 seconds or "latching", meaning activation "on", activation "off"
- Receiver voltage input 12~30 VDC

## Applications



Swing doors



Sliding doors



Glass stone or  
marble surfaces



## Technical Specifications

Part numbers:	912 -WBT	912N-WBT	912GL-WBT	912-R (Receiver)
Power Input AA batteries	6VDC	3VDC	3VDC	12-30VDC
Style	Double-gang	Mullion	Surface Applied	N/A
Static Current	80mA	80mA	80mA	30mA
Main Contact Capacity	N/A	N/A	N/A	3A @ 30VDC SPDT
Battery Life	Approx. 450 days*	Approx. 250 days*	Approx. 250 days*	N/A
Emission Current	10mA	10mA	10mA	N/A
Infrared Modulation Frequency	38KHz	38KHz	38KHz	N/A
Infrared Scanning Interval	100ms	100ms	100ms	N/A
Response time	≤130ms	≤130ms	≤130ms	≤130ms
Transmitter Range	100' (30m)	100' (30m)	100' (30m)	N/A
Dimensions	5" x 5" x 1.75"	4.75" x 2" x 1.75"	3.375" x 3.375" x 0.565"	4.8" x 1.96" x 1.25"
Certification	FCC			
Working Temperature	-43°F ~ 113°F	-43°F ~ 113°F	-43°F ~ 113°F	-43°F ~ 113°F
Working Humidity	10-90%RH	10-90%RH	10-90%RH	10-90%RH

Switches can be purchased individually or with accompanying receivers. Check the catalog or price book for order details.

Copyright © 2021 dormakaba Canada Inc. Information on this sheet is intended for general use only. \*Battery average lifespan with quality batteries. dormakaba reserves the right to alter designs and specifications without notice or obligation.