

ENFORCER® PUSH-TO-EXIT PLATES

SD-7202GC-PEQ

- ▶ Stainless-steel, single-gang.
- ▶ 2" square, green, illuminated, momentary push button.
- ▶ Includes: "PUSH TO EXIT" & "PRESIONE PARA SALIR."
- ▶ N.O./N.C. contacts rated 10 Amps @ 125 ~ 250 VAC.
- ▶ Includes color-coded leads.

SD-7103GC-PEQ

- ▶ Stainless-steel slimline plate.
- ▶ Green illuminated momentary button ($1\frac{5}{16} \times 1\frac{11}{16}$ ").
- ▶ Long-life green 12V LED.
- ▶ Includes: "PUSH TO EXIT" & "PRESIONE PARA SALIR."
- ▶ N.O./N.C. contacts rated 5 Amps @ 125 ~ 250 VAC.

SD-7202BC-HC

- ▶ Stainless-steel, single-gang plate.
- ▶ 2" square, blue, illuminated, momentary push button.
- ▶ Handicap symbol.
- ▶ N.O./N.C. contacts rated 10 A @ 125 ~ 250 VAC.
- ▶ Includes color-coded leads.

Spanish & English messages included



SD-7201GCPE1Q

- ▶ Stainless-steel single-gang plate.
- ▶ Green, $1\frac{1}{2}$ " dia., mushroom-cap push button.
- ▶ "Exit" and "Salida" silk-screened on plate.
- ▶ N.O./N.C. contact rated 5A @ 125VAC.



SD-7101KBPE1Q

- ▶ Stainless-steel slimline plate.
- ▶ Black momentary push-button switch.
- ▶ "Exit" and "Salida" silk-screened on plate.
- ▶ N.C. contact rated 1A @ 125VAC.



SD-7204SGEX1Q

- ▶ Stainless-steel single-gang plate.
- ▶ Vandal-resistant, 1" dia., stainless-steel pushbutton.
- ▶ "Exit" and "Salida" silk-screened on plate.
- ▶ N.O./N.C. contact rated 5A @ 250VAC.



NEW

SD-7104SGEX1Q

- ▶ Stainless-steel slimline plate.
- ▶ Vandal-resistant, 1" dia., stainless-steel pushbutton.
- ▶ "Exit" and "Salida" silk-screened on plate.
- ▶ N.O./N.C. contact rated 5A @ 250VAC.

NEW



The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.