

RA-4961-MBQ

Wireless Mailbox/Tilt Sensor

Features:

- For use with the RA-4961 series receivers
- Wirelessly monitor mailboxes or any tilting motion
- Up to 1,000ft (305m) transmission range*
- Mounts to standard mailbox flaps or other flat surfaces that may tilt
- Adhesive mount – no screws required
- Adjustable sensing angle



RA-4961-MBQ

Specifications:

Model Number	RA-4961-MBQ	
Frequency	914.8MHz	
Transmission range*	Up to 1,000ft (305m)	
Channels	1	
Power supply	1x 12V/23A Battery (Included)	
Current	Standby	3.5µA
Draw	Max	22mA
Estimated battery life	365 days (3 triggers/day)	
Low battery indicator	Zone LED on receiver blinks continuously	
IP rating	IP45	
Operating Temperature	-4°~140°F (-20°~60°C)	
Dimensions	5"x1"x3/4" (126x25x18mm)	

*Line of sight. Transmission range will vary depending on installation and operating environment.

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright 2015 © SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI®

PI_RA-4961MBQ_151210.docx