

Emergency & Holdup Devices

SS-077Q/SS-078Q Holdup Buttons



- Latching pushbutton, flag shows when pressed, two reset keys included.
- High-impact ABS case, stainless-steel cover.
- SPST switch rated 1A@12VDC.
- **SS-077Q** – N.C. (push-to-open) operation.
- **SS-078Q** – N.O. (push-to-close) operation.
- **SS-078-KEYQ** – Spare key for SS-077Q/078Q.

SS-074Q Momentary Holdup Button



- N.O. (push-to-close) momentary contact.
- Double-button operation virtually eliminates accidental triggering.
- Sturdy metal case, silver-plated SPST contacts, pre-wired for quick installation.
- Rated 1A@25VDC.

SS-075Q / SS-075CQ Emergency Buttons



- **SS-075Q** — N.O. (push-to-close) momentary contact.
- **SS-075CQ** – N.O. or N.C. (selectable) momentary contact.
- SPST contact rated 0.5A@25VDC.
- Large button has “EMERGENCY” printed on face.
- Screw terminals.

SS-075C-PEQ NO/NC Emergency Button



- Includes three stick-on labels (“PUSH TO EXIT,” “PRESIONE PARA SALIR,” and “EMERGENCY”). Choose the label that best fits the application.
- Mounting screw terminals (screws included).
- N.O. or N.C. (selectable) momentary contact.
- Contact rated 0.5A@12VDC.