


HD-TVI 2MP Intense IR Bullet Cameras with Junction Box

HT7040T 2.8-12mm auto iris varifocal lens, dark gray housing

HT7041T 3.6mm fixed lens, dark gray housing



Features

- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30fps
- True WDR operation
- Intense IR function – no saturation, IR intensity adapts to subject to provide vivid image
- True day/night operation – mechanical IR cut filter
- Built-in heater and anti-fog glass reduces condensation
- 3 axis lens mount
- Full OSD operation through on-board control and UTC (up the coax)
- Additional 960H analog output (HT7041T)
- Signal distance up to 1600 feet*
- 12VDC & 24VAC dual voltage operation
- Vandal / tamper resistant
- IP67 compliant, weather resistant
- 5 year warranty

Camera Specifications

Image Sensor	1/3" Sony Exmor CMOS, 2MP
Minimum Illumination.....	0.001 lux
Effective Pixels	1984 (H) x 1105 (V)
Total Pixels	2000 (H) x 1121 (V)
Scanning System.....	Progressive
IR Range	98 ft. (depending on scene reflection)
Intense IR	0 – 20 (adjustable)
S/N Ratio	More than 50dB
Output Resolution.....	1920x1080 @ 30fps / 1280x720 @ 60fps
Video Output.....	1.0Vp-p / 75 Ohms
Electronic Shutter	Auto / Manual (1/30 – 1/30,000 sec.) / Flicker
WDR.....	On (Low / Middle / High) / Off
Day / Night.....	Auto / Color / BW / External
White Balance	Auto / AWB / AWC-Set / Manual
Brightness.....	0 – 20 (adjustable)
AGC.....	0 – 20 (adjustable)
Sense-up	2x – 32x (adjustable)
Backlight.....	BLC / HSBLC
Motion Detection.....	On / Off (4 zones)

Camera Specifications (continued)

Privacy Masking	On / Off (16 zones)
Mirror	On / Off
V-Flip	On / Off
Sharpness	0 – 20 (adjustable)
Lens Shading.....	On / Off
DNR.....	Off / Low / Middle / High
Test Monitor Output	CVBS
Communication.....	UTC (up the coax)

Operating & Unit Specifications

Power	12VDC / 24VAC dual voltage (power supply not included)
Power Consumption	12VDC, 720mA max. / 24VAC, 260mA max.
Operating Temperature.....	-4°F – 140°F
Operating Humidity.....	20% - 95% RH
Unit Dimensions	3.94" (W) x 3.94" (H) x 8.27" (L)
Unit Weight	3.1 lbs.
Certifications.....	FCC, RoHS

Optional Accessories



INTJBS
Square
Junction Box



INTCM
Corner/Pole
Adapter



CVCJBB
Bullet Camera
Junction Box



PSW4
24VAC
Power Supply



PSW5
12VDC
Power Supply



TVIUTPPT
HD Video
Transceiver with
Pigtail (Balun)



TVIUTP
HD Video
Transceiver

*To preserve signal quality and distance, Speco Technologies recommends using coax with a 100% copper center conductor and at least 95% braided copper shield. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/20/16