

## HTD8TG

2.8mm fixed lens, dark gray housing



### Features

- Supports up to 8MP @15fps
- Built-in high powered IR LEDs
- Digital WDR (wide dynamic range) operation
- IP66 compliant, weather resistant
- 12VDC (power supply not included)
- Junction box included for convenience
- 5 year warranty



Included Junction Box



### Camera Specifications

Max Aperture	F=1.6
Focal Control	Manual
Image Sensor	Progressive Scan, 1/2.0" CMOS Sensor, 8MP
Effective Pixels	3840(H)x2160(V)
Maximum Resolution	3864x2176
Minimum Illumination	0.1 lux
White Balance	AWB/ATW/AWC
WDR	DWDR/OFF/AUTO
Day/Night	IR Cut Filter/Auto/Color/B&W/EXT
DNR	2D-DNR/3D-DNR (Low/Middle/High)
Output	TVI
S/N Ratio	52dB (AGC OFF)
Frame Rate	8MP @15fps

### Video Specifications

Main Resolution	3840x2160 @15fps
TV System	NTSC
Brightness	1 ~ 100
Motion	ON/OFF
Shutter	AUTO/FLK
Mirror/Flip	OFF/MIRROR
Color Gain	Blue Gain/Red Gain (1 ~ 10)
AGC (Auto Gain Control)	0 ~ 15
IR Distance	6pcs Super LEDs (66ft)
Remote Control Interface	UTC

### Operating & Unit Specifications

Power	12VDC (power supply not included)
Power Consumption	Max. 5W
Operating Temperature	14°F ~ 122°F
Unit Weight	0.7 lbs

### Optional Accessories



PSW5  
12VDC  
Power Supply



INT4WM  
Wall Mount



TVIUTPPT  
HD Video  
Transceiver with  
Pigtail (Balun)



TVIUTP  
HD Video  
Transceiver