

Speed Dome Keyboard Controller

KBDPTZ1

Features

- Capable of controlling up to 32 speed domes
- 2 levels of passwords (administrator and user) are supported for higher security
- Programmed data from up to 2 domes can be downloaded to non-volatile memory space and uploaded to a new dome
- Control a camera's panning and tilting movement with variable speeds from 0.5°/sec. to 90°/sec., as well as its zoom, focus and iris command
- Normal speed is inversely proportional to the current zoom ratio
- Turbo speed is max. 380°/sec. when "Ctrl" key is pressed
- Define and recall up to 240 presets, which are immediate camera call-ups of preset position view with automatic zoom and focus
- Able to define and run up to 8 patterns comprising of a sequential series of pan, tilt, zoom and focus movements from a single camera
- Define and run up to 8 scans which scan between 2 limits
- Incorporate up to 300 presets, patterns, scans and 8 tours
- Presets, patterns and scan are automatically displayed one after the other on the main monitor
- Programmable user preferences (alarm, preset, title, etc.)



Specifications

Power Consumption12VDC, 0.5W
 Control MethodRS-485
 Baud RatesRS-485 2400 - 230K bps
 Dimensions15" (W) x 6.5" (L) x 2.75" (H)
 Weight2.5 lbs.
 Power Supply12VDC@1.5A (power supply included)

Controls the following dome cameras:

HTSD10X	CPTZ29D5W	O2PTZ22D5W
HTSD12X	CPTZ32D5W	OPTZ33D5W
HTSD37X	OPTZ36XO	OPTZ34D5W
CPTZ28D5W	OPTZ36XI	

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/7/14