

## VLDT3GM

2.8-12mm varifocal motorized lens, dark gray housing

## VLDT3WM

2.8-12mm varifocal motorized lens, white housing



### Features

- 1/2.9" 2MP Sony CMOS
- Supports multiple video signal outputs (TVI / AHD / CVI / CVBS)\*
- 18 built-in IR LEDs
- IP66 compliant, weather resistant
- Full OSD operation through UTC (up the coax)
- Junction box included
- UL Listed
- 5 year warranty



Camera Specifications	
Image Sensor	1/2.9" 2MP Sony CMOS
Maximum Resolution	1920x1080
Minimum Illumination	0 lux
Number of IR LEDs	18
IR Distance	Up to 65 ft. (depending on scene reflection)
White Balance	ATW
Blacklight Compensation	Auto
Electronic Shutter Speed	NTSC: 1/60-1/100,000 PAL: 1/50-1/100,000
AGC	On/Off
DNR	On/Off
WDR	On/Off
Day/Night	Auto / Color / BW / EXT
OSD	UTC
Gamma	0.45 typ.
Scanning System	Progressive
Video Signal Output	HD-TVI / AHD / CVI / CVBS

Operating Specifications	
Power Supply	12VDC (power supply not included)
Power Consumption	Max. 430mA
Operating Temperature	-22°F - 104°F
Storage Temperature	-22°F - 104°F
Unit Dimensions	4.72" (W) x 3.94" (H)
Unit Weight	1.74 lbs.

### Optional Accessories

<p><b>TVIUTPPT</b> HD Video Transceiver with Pigtail (Balun)</p>	<p><b>TVIUTP</b> HD Video Transceiver</p>	<p><b>PSW5</b> 12VDC Power Supply</p>
----------------------------------------------------------------------	-----------------------------------------------	-------------------------------------------

\*Cameras are defaulted to HD-TVI. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 12/11/17