



HD-TVI 2MP IR Motorized Dome Camera with Junction Box

VLDT6M

2.8-12mm motorized lens, white housing



Features

- Full HD resolution over coax (HD-TVI)
- 30 built-in IR LEDs
- Supports up to Full HD 1080p @30fps
- Signal distance up to 1600 ft.
- Multi-format HD (TVI, CVI, AHD, CVBS)*
- True WDR
- Motorized lens
- Full OSD operation through UTC (up the coax)
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- 5 year warranty



Included Junction Box



Camera Specifications	
Image Sensor	1/2.8" CMOS
Maximum Resolution	1920 x 1080
Minimum Illumination	Color: 0.001lux @ F1.2
S/N Ratio	greater than 52dB
Motion Detection	Yes
Number IR LEDs	30
IR Range	98' (depending on scene reflection)
Day/Night	IR cut filter
DNR	Yes
Video Output	TVI / CVI / AHD / CVBS
Field of View (Horizontal)	99.8° - 36.8°
Field of View (Vertical)	67.4° - 21.2°

Operating & Unit Specifications	
Power	12VDC (power supply not included)
Power Consumption	IR on (less than 1W) IR off (less than 4W)
Operating Temperature	-4°F - 104°F
Unit Dimensions	5.7" (Dia.) x 4.5" (L)
Unit Weight	2.1 lbs.

Optional Accessory

O4D6WM
Dome Wall Mount

PSW5
12VDC Power Supply

TVIUTPPT
HD Video Transceiver with Pigtail (Balun)

TVIUTP
HD Video Transceiver

CMT1
Corner Mount (use with wall mount)

PMT1
Pole Mount (use with wall mount)

CLT4
Ceiling Mount

*Camera defaulted to HD-TVI. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/24/20