



4 Channel Surveillance Kit with Three 5MP IP Cameras and One 8MP Advanced Analytics Camera, 1TB

ZIPK4TA

4 Channel Network Video Recorder with Built-In PoE
3 5MP IP Cameras
1 8MP Advanced Analytics IP Camera



Front panel



Rear panel



Key Features

- EZ Wizard:** for easy network and system setup
- EZ Search:** search events from thumbnails
- EZ Record:** set up recording resolutions and recording type
- EZ Copy:** copy what you are playing onto a USB flash drive
- EZ App Setup:** just scan a QR code with the app to view your cameras on your mobile device

Recorder Features

- Up to 8MP resolution for live view, recording, and playback
- Plug & Play – get video automatically via the PoE ports without any setup
- Facial Recognition and Comparison*
- Human and Vehicle Detection*
- Supports H.265 and H.264 streams
- Free US-based DDNS service
- 4K monitor output
- Gigabit Ethernet port
- Built-in S.M.A.R.T technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- Remote monitoring via PC and mobile apps
- 1TB storage
*use with O8K1A

Camera Features: (Only works with this kit)

- Supports up to 5MP resolution (O5K1)
- Supports up to 8MP resolution (O8K1A)
- 2.8mm wide angle lens
- True Day/Night operation (IR cut filter)
- IR range up to 100ft (built-in IR LEDs)
- Supports H.265/H.264 compression
- IP66 compliant, weather resistant
- Includes Micro SD card slot up to 128GB

What's in the box:

- NVR with 1TB hard drive
- Three 5MP cameras
- One 8MP Advanced Analytics camera
- Three 60ft Ethernet cables
- One 3ft Ethernet cable
- Remote control
- 2 x AAA Batteries
- HDMI cable

Camera Specifications	O5K1	O8K1A
Image Sensor	1/2.7" 5MP CMOS	1/2.7" Progressive CMOS
Resolution	2592 x 1944	8MP 3840(H)×2160(V)
Minimum Illumination	0 lux (IR LED on), F1.2	Color 0.05lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
Day/Night	IR cut filter	IR cut filter with auto switch Day/Night/Auto/Schedule
Compensation	DWDR/BLC	Off/On (5 Zone)
White Balance	Auto / Manual/Indoor	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000 sec	1/5 ~ 1/20000s
DNR	3D	3D
IR Range	100ft. (depending on scene reflection)	100ft. (depending on scene reflection)
Compression	H.265, H.264	H.265, H.264
Bitrate Control	VBR, CBR	VBR, CBR
Multiple Streaming	2 streams	2 streams
Ethernet	10/100 Mbps	10/100 Mbps
Power	PoE or 12VDC (power supply not included)	PoE or 12VDC (power supply not included)
Power Consumption	~7W	~7W
Operating Temperature	-22°F - 131°F	-22°F - 140°F
Operating Humidity	0% - 90% RH	0% - 95% RH
Unit Dimensions	3.35" (H) x 3.55" (Dia.)	3.94" (H) x 3.56" (Dia.)
Unit Weight	1.5 lbs.	1.5 lbs.
Alerts & Advanced Analytics	Motion Detection	Motion Detection, Human Detection, Vehicle Detection, Facial Recognition

Recorder Specifications	
Max. Bit Rate	40 Mbps
Max. Recording Resolution	8MP
PoE Ports	4
Monitor Output	1 HDMI, 1 VGA
Display Resolutions	3840 x 2160, 2560 x 1440, 1920 x 1080, 1440 x 900, 1290 x 1024, 1280 x 720, 1024 x 768
USB Ports	2 x USB 2.0
HDD Slots	1 (Up to 1TB)
Ethernet	RJ-45 (100/1000M) port
Remote Viewing	Speco Gray Viewer (Windows), Speco Gray app (iOS, Android)
Power Supply	48VDC, 1.2A
Dimensions	11.8" (W) x 2.1" (H) x 8.9" (D)
Model	N4JLA

Optional Accessories



O5KJBD
Camera Junction Box



O5KWMT
Wall Mount



RESI-CAM®

Hard drives excluded. iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec. Rev. 6/14/21